

INDUSTRY SLIM LED 590MM 7100LM 850 IP66 46X117D LS2 (47W)

DETAILED CARD



INDUSTRY SLIM LED 590MM 7100LM 850 IP66 46X117D LS2 (47W)

DETAILED CARD

TECHNICAL PARAMETERS

Ingress protection:	IP66
Rated power of the luminaire [W]*:	47
Luminous flux [lm]*:	7100
Colour temperature [K]:	5000
Material of the body:	aluminium
Colour of the body:	grey
Diffuser material:	PC
Diffuser type:	Clear
Optics material:	PC
Mounting version:	surface, suspended

CHARACTERISTICS

Industry Slim Led - a brand new industrial luminaire is characterized by high luminous flux and very high luminous efficiency >160 lm/W, which makes this luminaire highly energy-efficient and environmentally friendly. It is distinguished by its very high IP66 tightness. It owes this tightness to its well-thought-out design. The polycarbonate diffuser is permanently attached to the housing with a durable silicone gasket. This means that in addition to the tightness thus achieved, the light module is protected from uncontrolled interference and access to the LEDs. The tightness of the lamp, is ensured by the gland, which screwed tightens the gasket and prevents the penetration of dust or moisture and water. Industry Slim Led allows for pendant or surface mounting.

APPLICATION

The luminaire is designed to illuminate industrial and warehouse facilities, due to its minimal dimensions, also in hard-to-reach places. The Industry Slim Led luminaire is available in various versions: with different optics, wide, narrow, and dedicated to high-bay light distribution, and five types of the diffuser, including an anti-glare diffuser.

DETAILS



INDUSTRY SLIM LED 590MM 7100LM 850 IP66 46X117D LS2 (47W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	935305	LED lifespan L90B10 [h]:	52000
Rated power of the luminaire [W]:	47	Diffuser material:	PC
EAN:	5905963935305	Optics:	46/117D
Colour temperature [K]:	5000	Optics material:	PC
Luminous flux [lm]:	7100	Material of the body:	aluminium
Supply voltage [V]:	220 - 240	Colour of the body:	grey
Beam angle [°]:	46/117	Dimensions (H/W/T/S) [mm]:	651/50/75
Frequency [Hz]:	50 - 60	Ingress protection:	IP66
Light distribution type:	corridor	Impact resistance:	IK09
Luminous efficacy [lm/W]:	151	Mounting version:	surface, suspended
Through wiring:	LS2	Working temperature [°C]:	from -25 to +35
Energy efficiency class:	C	Wire type:	5x1,5
Electrical protection class:	I	Net weight [kg]:	1.110
Colour rendering index:	>80	Warranty [years]:	5
SDCM:	≤ 3	CE certificate:	167/2023
LED lifespan L70B50 [h]:	171000	ENEC Certificate:	0362/ENEC/24
LED lifespan L80B20 [h]:	108000	Manual:	Download PDF
		Plik LDT:	

INDUSTRY SLIM LED 590MM 7100LM 850 IP66 46X117D LS2 (47W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
908200	TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2)
60000006	M16 stuffing box plug various PA black M-16 - BPM-21



TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) (908200)



M16 stuffing box plug various PA black M-16 - BPM-21 (60000006)

Card creation date: 05 August 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 167/2023