DETAILED CARD





DETAILED CARD

TECHNICAL PARAMETERS

Ingress protection: IP66

Rated power of the luminaire [W]*: 56

Luminous flux [lm]*: 7500

Colour temperature [K]: 4000

Material of the body: aluminium

Colour of the body: grey

Diffuser material: PC

Diffuser type: OPAL

Mounting version: surface, suspended

CHARACTERISTICS

Industry Slim Led - a brand new industrial luminaire is characterized by high luminous flux and very high luminous efficiency >160 lm/W, which makes this luminaire highly energy-efficient and environmentally friendly. It is distinguished by its very high IP66 tightness. It owes this tightness to its well-thought-out design. The polycarbonate diffuser is permanently attached to the housing with a durable silicone gasket. This means that in addition to the tightness thus achieved, the light module is protected from uncontrolled interference and access to the LEDs. The tightness of the lamp, is ensured by the gland, which screwed tightens the gasket and prevents the penetration of dust or moisture and water. Industry Slim Led allows for pendant or surface mounting.

APPLICATION

The luminaire is designed to illuminate industrial and warehouse facilities, due to its minimal dimensions, also in hard-to-reach places. The Industry Slim Led luminaire is available in various versions: with different optics, wide, narrow, and dedicated to high-bay light distribution, and five types of the diffuser, including an anti-glare diffuser.

DETAILS




DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	933332
EAN:	5905963933332
Rated power of the luminaire [W]:	56
Luminous flux [Im]:	7500
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Luminous efficacy [lm/W]:	134
Energy efficiency class:	D
Electrical protection class:	1
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
LED lifespan L70B50 [h]:	93000
LED lifespan L80B20 [h]:	59000
LED lifespan L90B10 [h]:	29000
Beam angle [°]:	105

Diffuser material:	PC	
Material of the body:	aluminium	
Colour of the body:	grey	
Dimensions (H/W/T/S) [mm]:	621/50/75	
Ingress protection:	IP66	
Impact resistance:	IK09	
Mounting version:	surface, suspended	
Working temperature [°C]:	from -25 to +35	
DIMM DALI:	yes	
Net weight [kg]:	1.800	
Light distribution type:	symmetric	
Warranty [years]:	5	
CE certificate:	167/2023	
ENEC Certificate:	0362/ENEC/24	
Manual:	Download PDF	
Plik LDT:	Download	

LIGHT CURVES





DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
908200	TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2)
6000006	M16 stuffing box plug various PA black M-16 - BPM-21



TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) (908200)



M16 stuffing box plug various PA black M-16 - BPM-21 (6000006)

