


# BARIS 52 LED DIR/IND IOT BT PIR HYT 1423MM 3450/2300LM 830 I CL. DALI PLX ANODA CO 36W/22W SINGLE SENSOR WITH SWITCH

## DETAILED CARD



## TECHNICAL PARAMETERS

Ingress protection:	IP40
Impact resistance:	IK06
Nominal power [W]:	58
Luminous flux [lm]*:	5950
Colour temperature [K]:	3000
Material of the body:	aluminium
Colour of the body:	grey
Diffuser material:	PC
Diffuser type:	OPAL
Mounting version:	suspended

## CHARACTERISTICS

Baris 52 LED IoT is a modern suspended lamp that combines elegant design with advanced technology. The modular design makes it easy to service and the unique suspension system ensures simple installation. Available with mounting box or optional plug-in socket.

**characteristics** The IoT BT PIR HYT DALI version has: a built-in BT HYT module that allows you to program functions in the Lena Lighting Clue app and control in real time; PIR motion and daylight sensor and DALI driver for dimming the light source.

## APPLICATION

The luminaire is dedicated to indoor use. It is used as a source of light for offices requiring focussed eyesight where low UGR and illumination of dark areas (e.g. ceilings) are required. The unique design, energy-efficient LED modules, and the possibility of cooperation with external lighting control systems in the DALI standard dedicate the luminaire to be used in modern office buildings of A+ class, with particular consideration for offices, representative rooms, conference halls, and passageways.

Baris 52 LED DIR/IND Single, as the name suggests, is a single luminaire with a pre-determined length. To create a line of length up to 6 meters without joining the profile and up to 25 meters without joining the diffuser allows version BARIS 52 LED.


# BARIS 52 LED DIR/IND IOT BT PIR HYT 1423MM 3450/2300LM 830 IP40 I CL. DALI PLX ANODA CO 36W/22W SINGLE SENSOR WITH SWITCH

## DETAILED CARD

### TECHNICAL PARAMETERS TABLE

Index:	932700	Material of the body:	aluminium
EAN:	5905963932700	Colour of the body:	grey
Light source:	LED module	Dimensions (H/W/T/S) [mm]:	1423/69/52
Rated power of the luminaire [W]:	58	Impact resistance:	IK06
Luminous flux [lm]:	5950	Ingress protection:	IP40
Supply voltage [V]:	220 - 240	Mounting version:	suspended
Frequency [Hz]:	50 - 60	Working temperature [°C]:	from -25 to +35
Luminous efficacy [lm/W]:	98	DIMM DALI:	yes
Energy efficiency class:	F	Version:	BT PIR HYT DALI
Electrical protection class:	I	Net weight [kg]:	2.800
Colour temperature [K]:	3000	Warranty [years]:	5
SDCM:	3	CE certificate:	<a href="#">227/2023</a>
LED lifespan L70B50 [h]:	111500	PZH certificate:	<a href="#">B-BK-60112-0357/2023</a>
LED lifespan L80B20 [h]:	70400	Manual:	<a href="#">Download PDF</a>
LED lifespan L90B10 [h]:	34000	Environmental Product Declaration (EPD):	<a href="#">852/2025</a>
Diffuser material:	PC	Category of application:	office lighting
Diffuser type:	OPAL	Plik LDT:	<a href="#">Download</a>
Diffuser colour:	milky		

### LIGHT CURVES



Card creation date: 16 December 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 227/2023