


SOLANTO Z 1200MM 3900LM 830 IP20 I CL. OPAL BLACK 62W

DETAILED CARD



TECHNICAL PARAMETERS

Light source:	LED module
Rated power [W] - range:	62
Colour temperature [K]:	3000
Luminous flux of the luminaire [lm] - range:	3900
Ingress protection:	IP20
Electrical protection class:	I
Diffuser material:	PMMA
Diffuser type:	OPAL
Colour of the body:	black

CHARACTERISTICS

Suspended or surface-mounted ring-shaped LED luminaire, allowing for an attractive arrangement of representative interiors. The luminaire is made of steel powder coated in white, black or other color to fit the character of the interior. The milky diffuser made with thermoforming method emphasises the decorative character of the luminaire. The pendant option includes a complete pendant system with a central box.

Multi LED versions allow you to choose from 4 flux and power settings increasing the versatility and functionality of the luminaire, while reducing the number of indexes to the necessary minimum.

APPLICATION

SOLANTO is an extremely glamorous pendant or surface mounted luminaire, dedicated to such interiors as lobbies, receptions, shopping malls, showrooms. It can be also used in apartments and apartments, perfectly fitting into stylish surroundings.

SOLANTO Z 1200MM 3900LM 830 IP20 I CL. OPAL BLACK 62W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	467936	LED lifespan L90B10 [h]:	34000
EAN:	5905963467936	Diffuser material:	PMMA
Light source:	LED module	Diffuser type:	OPAL
Rated power [W] - range:	62	Material of the body:	Steel
Luminous flux of the luminaire [lm] - range:	3900	Colour of the body:	black
Supply voltage [V]:	220 - 240	Ring colour:	black
Frequency [Hz]:	50 - 60	Dimensions (H/W/T/S) [mm]:	ø1200/32
Luminous efficacy [lm/W]:	63	Mounting dimensions [mm]:	340/340
Energy efficiency class:	G	Ingress protection:	IP20
Electrical protection class:	I	Mounting version:	suspended
Colour temperature [K]:	3000	Cable length [m]:	1.35
Colour rendering index:	>80	Net weight [kg]:	5.800
SDCM:	≤ 3	Warranty [years]:	5
LED lifespan L70B50 [h]:	112000	CE certificate:	218/2023
LED lifespan L80B20 [h]:	70 000	Manual:	Download PDF

Card creation date: 02 October 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 218/2023