# TOWER LITE LED

DETAILED CARD



## TECHNICAL PARAMETERS

| | |
|---|---|
| **Ingress protection:** | IP54 |
| **Impact resistance:** | IK07 |
| **Rated power of the luminaire [W]*:** | 94 |
| **Luminous flux [lm]*:** | 9200 |
| **Colour temperature [K]:** | 4000 |
| **Energy efficiency class:** | E |
| **Material of the body:** | PP |
| **Colour of the body:** | graphite |
| **Diffuser material:** | PC |
| **Diffuser type:** | OPAL |

## CHARACTERISTICS

Set of compact floodlights providing uniform and stable directional lighting. Lamp body made of co-polymer with rubber for high durability. Lamps equipped with an anti-glare frosted PC diffuser with UV stabilizer, transmitting, despite the matt surface, up to 80% of the light emitted by the diodes, providing a soft and diffused light. Set behind a 2 meter stand allowing easy placement of the light and selection of the right angle for the work surface.
Stand parameters:
- Stand: height unfolded / folded: 200 cm / 108 cm
- Leg spacing: 92 cm
- tube diameter (legs): 3.5 cm
- maximum load: 15 kg

## APPLICATION

Thanks to various functions the lamp is an ideal solution for lighting all workplaces. High luminous flux and maximum degree of impact resistance are particularly important in illumination of construction sites or in the work of services intervening at various emergencies. High degree of waterproofness allows for its use in the most difficult weather conditions. Multi-position arm and numerous accessories provide a wide range of mounting options so as to precisely direct the light beam leaving the hands of the worker free. Small size and low weight make it easy to use in workshops, car showrooms, to illuminate the workplace in industrial halls or finishing works.

# TOWER LITE LED

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

| | | | |
|---|---|---|---|
| **Index:** | 622359 | **Dimensions (H/W/T/S) [mm]:** | 2 x 236/261/64 |
| **Light source:** | LED module | **Impact resistance:** | IK07 |
| **Rated power of the luminaire [W]:** | 94 | **Ingress protection:** | IP54 |
| **Luminous flux [lm]:** | 9200 | **Plug type:** | UNI-SCHUKO |
| **Energy efficiency class:** | E | **Cable length [m]:** | 3 |
| **Colour temperature [K]:** | 4000 | **Net weight [kg]:** | 1 |
| **Diffuser material:** | PC | **Manual:** | Download PDF |
| **Diffuser type:** | OPAL | **CE certificate:** | 188/2023 |
| **Material of the body:** | PP | **Category type:** | floodlights, workplace floodlights |
| **Colour of the body:** | graphite | | |

Card creation date: 26 April 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 188/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl