

# TERRANO 600X30MM 2300LM 830 II CL. BLACK 60D (22W)

DETAILED CARD



## TECHNICAL PARAMETERS

Light source:	moduł LED
Rated power of the luminaire [W]*:	9
Luminous flux [lm]*:	1050 - 6300
Energy efficiency class:	G
Electrical protection class:	II
Colour temperature [K]:	3000; 3500; 4000
Colour of the body:	biały; czarny

## CHARACTERISTICS

The new linear luminaire in the form of a compact louver with LEDs and focusing lenses enables extremely effective glare reduction (UGR between 12 and 19). Terrano luminaires are characterised by excellent performance and many conveniences. Above all, it can be installed quickly on the supporting structure of a modular ceiling. The same luminaire can be relocated just as quickly. Changing the location will leave no trace of the mounting holes. For convenience and aesthetics, the luminaire has an extra-thin power cable, which fits between the structure and the ceiling tile. Terrano, a plastic luminaire in a slim steel housing, is available in two colour temperatures, 3000 K and 4000 K, and in two colours, white and black.

## APPLICATION

Terrano can be fitted directly into modular ceiling profiles to provide general lighting, but can also be used to spotlight selected elements of a space. Terrano will become both a striking element of modern arrangements where lighting plays a key role and a complement to subtle, minimalist spaces.

\*DUO- version of double lamp on one power supply


# TERRANO 600X30MM 2300LM 830 II CL. BLACK 60D (22W)

## DETAILED CARD

### TECHNICAL PARAMETERS TABLE

Index:	x	Diffuser colour:	transparentny
EAN:	x	Optics:	soczewka
Light source:	moduł LED	Optics material:	PMMA
Rated power of the luminaire [W]:	9	Material of the body:	blacha stalowa malowana proszkowo
Luminous flux [lm]:	1050 - 6300	Colour of the body:	biały; czarny
Frequency [Hz]:	50-60	Ingress protection:	IP20
Energy efficiency class:	G	Mounting version:	do profilu T sufitów podwieszanych
Electrical protection class:	II	Working temperature [°C]:	od -10 do +35
Colour temperature [K]:	3000; 3500; 4000	Dimensions (H/W/T/S) [mm]:	17/568/33
Colour rendering index:	>80; >90	Net weight [kg]:	0.390; 0.420; 0.650
SDCM:	≤ 3	Category type:	louvres
Beam angle [°]:	55	LED lifespan L70B50 [h]:	156000
Light distribution type:	symetryczny	LED lifespan L80B20 [h]:	98000
Surge protection [kV]:	1; 2	LED lifespan L90B10 [h]:	47000
Diffuser material:	PMMA	CE certificate:	<a href="#">304/2023; 60/2022</a>
Diffuser type:	matryca soczewkowa	Manual:	<a href="#">Download PDF</a>

### LIGHT CURVES



# TERRANO 600X30MM 2300LM 830 II CL. BLACK 60D (22W)


DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
937408	Terrano white connector
937415	Terrano black connector



Terrano white connector (937408)



Terrano black connector (937415)

Card creation date: 11 July 2022  
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 304/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl