TERRANO DUO 2X600X30MM 2X2200LM 840 II CL. BLACK 60D (34W)

DETAILED CARD





TECHNICAL PARAMETERS

Light source:	LED module
---------------	------------

Rated power of the luminaire [W]*: 34

Luminous flux [lm]*: 4400

Energy efficiency class: G

Electrical protection class:

Colour temperature [K]: 4000

Colour of the body: black

Dimensions (H/W/T/S) [mm]: 17/568/33

CHARACTERISTICS

The new linear luminaire in the form of a compact louver with LEDs and focusing lenses enables extremely effective glare reduction (UGR between 12 and 19). Terrano luminaires are characterised by excellent performance and many conveniences. Above all, it can be installed quickly on the supporting structure of a modular ceiling. The same luminaire can be relocated just as quickly. Changing the location will leave no trace of the mounting holes. For convenience and aesthetics, the luminaire has an extra-thin power cable, which fits between the structure and the ceiling tile. Terrano, a plastic luminaire in a slim steel housing, is available in two colour temperatures, 3000 K and 4000 K, and in two colours, white and black.

APPLICATION

Terrano can be fitted directly into modular ceiling profiles to provide general lighting, but can also be used to spotlight selected elements of a space. Terrano will become both a striking element of modern arrangements where lighting plays a key role and a complement to subtle. minimalist spaces.

*DUO- version of double lamp on one power supply



TERRANO DUO 2X600X30MM 2X2200LM 840 II CL. BLACK 60D (34W)


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	937170
EAN:	5905963937170
Light source:	LED module
Rated power of the luminaire [W]:	34
Luminous flux [Im]:	4400
Luminous efficacy [lm/W]:	129
Energy efficiency class:	G
Electrical protection class:	II
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
Beam angle [°]:	60
Light distribution type:	symmetric
Diffuser material:	PMMA
Diffuser type:	matrix led
Diffuser colour:	transparent

Optics:	lens
Optics material:	PMMA
Material of the body:	powder coated steel
Colour of the body:	black
Ingress protection:	IP20
Mounting version:	to T-profile ceilings suspended
Working temperature [°C]:	from -10 to +35
Dimensions (H/W/T/S) [mm]:	17/568/33
LED lifespan L70B50 [h]:	150000
LED lifespan L80B20 [h]:	100000
LED lifespan L90B10 [h]:	50000
Net weight [kg]:	0.650
Manual:	Download PDF
CE certificate:	68/2025
Category type:	luminaires and linear systems
Plik LDT:	Download

LIGHT CURVES






TERRANO DUO 2X600X30MM 2X2200LM 840 II CL. BLACK 60D (34W)


DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
937408	Terrano white connector
937415	Terrano black connector
583698	Terrano surface-mounted frame. matt black RAL9005, 573x38x60 – side opening + cable gland







Terrano black connector (937415)



Terrano surface-mounted frame. matt black RAL9005, 573x38x60 – side opening + cable gland (583698)

Card creation date: 02 June 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

