EXPO ADJUST SHOP N 2700LM ZOOM 22-55ST. WHITE 927 35W

DETAILED CARD





TECHNICAL PARAMETERS

Product line:	Bread
Light source:	СОВ
Rated power of the luminaire [W]*:	35
Luminous efficacy [lm/W]:	78
Energy efficiency class:	G
Electrical protection class:	1
Ingress protection:	IP20
Tilt angle adjustment [°]:	yes
Beam angle [°]:	22-55

CHARACTERISTICS

EXPO ADJUST SHOP are top quality aluminum projectors with LED COB light source. The projectors are available in versions that allow mounting on rails, as well as surface and flush mounting, such as in plasterboard ceilings. Mounting on a trunking system, increases the range of applications and allows the user to make arrangement changes even after installation. The compact, small-sized aluminum body with a heat sink effectively dissipates excess heat from the projector and increases the life of the product. The aesthetically pleasing ABS box effectively masks the power supply housed in it. Expo Adjust projectors are friendly to people and the environment. They are innovative, highly energy-efficient projectors with excellent light efficiency and a minimalist, distinctive design.

APPLICATION

The absence of ultraviolet and infrared emissions and the high colour rendering index, combined with the highest luminous efficacy and excellent product durability, allow EXPO ADJUST to be used wherever the highest quality of light is expected while maintaining energy efficiency. The main areas of application fall into the field of accent lighting in commercial buildings, museums, exhibition halls, offices, flats.

Meat and sausages - the colour of light is shifted closer to the colour we know as 'red' (Ra 80) meat products look more appetising (fresh and bloodier)

Bread - the colour of light shifted closer to the colour known as 'yellow' (3000K, Ra 90) bread is more saturated with colour, which makes it appear fresher and more appetising

Jewellery - a colour of light shifted closer to the colour we know as 'white' (4000K Ra 90) A universal colour for drawing attention to detail and better exposure



EXPO ADJUST SHOP N 2700LM ZOOM 22-55ST. WHITE 927 35W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

poduct line: ght source: coe ited power of the luminaire [W]: minous flux [Im]: phinous efficacy [Im/W]: phinous efficacy [Im/W]: ght source: 78	
content of the luminaire [W]: minous flux [Im]: minous efficacy [Im/W]: regy efficiency class: COE 35 270 78 G	
nted power of the luminaire [W]: 35 minous flux [Im]: 2700 minous efficacy [Im/W]: 78 ergy efficiency class: G	
minous flux [lm]: 2700 minous efficacy [lm/W]: 78 ergy efficiency class: G	
minous efficacy [lm/W]: 78 ergy efficiency class: G	
ergy efficiency class: G)
ectrical protection class:	
olour rendering index: 90	
OCM: ≤ 3	
D lifespan L70B50 [h]: 1000	000
D lifespan L80B20 [h]: 640	00
D lifespan L90B10 [h]: 3100	0
eam angle [°]: 22-5	5
ght distribution type: sym	
ffuser material: PC	metric

Diffuser type:	transparent
	·
Diffuser colour:	transparent
Optics:	lens
Optics material:	PC
Material of the body:	aluminium
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	225/213/95
Ingress protection:	IP20
Mounting version:	surface
Working temperature [°C]:	from -20 to +30
Tilt angle adjustment [°]:	yes
Net weight [kg]:	0.730
Warranty [years]:	5
CE certificate:	215/2023
Manual:	Download PDF
Category type:	spotlight

Card creation date: 22 August 2025



