

BARIS 52 LED P GK CONNECTOR L 2100LM 840 IP20 I CL. PLX BLACK 17W

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---|------------|
| Index: | 936067 |
| Light source: | LED module |
| Rated power of the luminaire [W]*: | 17 |
| Frequency [Hz]: | 50 - 60 |
| Ingress protection: | IP20 |
| Energy efficiency class: | E |
| Electrical protection class: | I |
| Colour temperature [K]: | 4000 |
| Diffuser material: | PC |
| Diffuser type: | OPAL |

CHARACTERISTICS

The key feature of L, T, X connectors is that they are equipped with integrated electronics and a diffuser, thanks to which the profile route bends remain illuminated along the entire length. Body is made of anodized aluminium profile in grey or aluminium profile painted white or black (other colors available on request). The optical system is complemented by a dedicated, flexible opal cover that evenly illuminates the connector. There is no division into surface mounted and suspended versions, which make the solution more universal.

Connectors (T, X, L) are supplied with an OPAL diffuser.

Connectors T, X, L UGR, and PRM diffusers are available on request.

APPLICATION

BARIS 52 LED connectors in the shape of the letter L, T, X and straight connectors create extraordinary opportunities to configure the light line matched to the character and shape of the room, allowing you to create virtually unlimited straight sequences, figures and patterns.

BARIS 52 LED P GK CONNECTOR L 2100LM 840 IP20 I CL. PLX BLACK 17W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|---------------|--------------------------------|------------------------------|
| Index: | 936067 | LED lifespan L80B20 [h]: | 70 500 |
| EAN: | 5905963936067 | LED lifespan L90B10 [h]: | 34000 |
| Light source: | LED module | Diffuser material: | PC |
| Rated power of the luminaire [W]: | 17 | Diffuser type: | OPAL |
| Luminous flux [lm]: | 2100 | Diffuser colour: | milky |
| Frequency [Hz]: | 50 - 60 | Material of the body: | aluminium |
| Luminous efficacy [lm/W]: | 124 | Colour of the body: | black |
| Ingress protection: | IP20 | Mounting version: | recessed |
| Energy efficiency class: | E | Dimensions of single box [mm]: | 100/680/700 |
| Electrical protection class: | I | Net weight [kg]: | 1.900 |
| Colour temperature [K]: | 4000 | Warranty [years]: | 5 |
| Colour rendering index: | >80 | CE certificate: | 343/2023 |
| LED lifespan L70B50 [h]: | 112000 | Manual: | Download PDF |

LIGHT CURVES



Card creation date: 02 November 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric and electronic waste equipment regulations (WEEE).

Certificate CE - Nr: 343/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl