

# BARIS SQUARE 52 LED Z 1453X1453MM 14500LM 840 IP40 I KL. PLX GRAY RAL9006 145W

DETAILED CARD



## TECHNICAL PARAMETERS

Light source:	moduł LED
Rated power of the luminaire [W]*:	32
Luminous flux [lm]*:	3100 - 15100
Energy efficiency class:	E; F
Electrical protection class:	I
Impact resistance:	IK06
Ingress protection:	IP40
Colour temperature [K]:	3000; 4000
Colour of the body:	biały; czarny; szary
Dimensions (H/W/T/S) [mm]:	1173/1173/69; 1453/1453/69; 613/613/69; 893/893/69

## CHARACTERISTICS

Baris Square 52 Led is a striking pendant lamp. Its classic shape fits perfectly into modern design. The lamp body is made of anodized aluminum profile in gray or aluminum profile painted in white or black (other colors available on request). The lamp is offered with two types of lampshade - prismatic or milky. The availability of the lamp in four sizes allows you to design the distribution of lighting in an individually tailored way. Lamps of different sizes and hung at different lengths can create an unlimited number of lighting compositions in the room.

## APPLICATION

The lamp is dedicated for indoor use. It is used as a source of main light in representative rooms, hotels, restaurants, conference rooms. The unique design and energy-saving LED modules also dedicate the lamp for use in modern office buildings or where the requirement is IP40 protection.

# BARIS SQUARE 52 LED Z 1453X1453MM 14500LM 840 IP40 I KL. PLX GRAY RAL9006 145W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	x	Light distribution type:	open space
EAN:	x	Surge protection [kV]:	1
Light source:	moduł LED	Diffuser material:	PC
Rated power of the luminaire [W]:	32	Diffuser type:	OPAL; clear
Luminous flux [lm]:	3100 - 15100	Diffuser colour:	mleczny; pryzmatyczny
Supply voltage [V]:	220-240	Material of the body:	aluminium
Frequency [Hz]:	50-60	Colour of the body:	biały; czarny; szary
Energy efficiency class:	E; F	Dimensions (H/W/T/S) [mm]:	1173/1173/69; 1453/1453/69; 613/613/69; 893/893/69
Electrical protection class:	I	Mounting dimensions [mm]:	160/40; 260/70
Colour temperature [K]:	3000; 4000	Impact resistance:	IK06
Colour rendering index:	>80	Ingress protection:	IP40
SDCM:	≤ 3	Mounting version:	zwieszany
Power factor:	0.92	Working temperature [°C]:	od -25 do +35
LED lifespan L70B50 [h]:	111500	Warranty [years]:	5
LED lifespan L80B20 [h]:	70400	CE certificate:	<a href="#">210/2023</a>
LED lifespan L90B10 [h]:	34000	Manual:	<a href="#">Download PDF</a>

Card creation date: 31 August 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 210/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)