


BARIS SQUARE 40 LED Z 1162X1162MM 15475LM PLX I CL. IP20 830 116W BLACK

DETAILED CARD



TECHNICAL PARAMETERS

Light source:	LED module
Rated power of the luminaire [W]*:	116
Luminous flux [lm]*:	15475
Energy efficiency class:	D
Electrical protection class:	I
Impact resistance:	IK06
Ingress protection:	IP20
Colour temperature [K]:	3000
Diffuser colour:	milky
Colour of the body:	black

CHARACTERISTICS

Baris Square 40 Led is a striking pendant lamp. Its classic shape fits perfectly into modern design. The lamp body is made of anodized aluminum profile in gray or aluminum profile painted in white or black (other colors available on request). The lamp is offered with two types of lampshade - prismatic or milky. The availability of the lamp in three sizes allows you to design the distribution of lighting in an individually tailored way. Lamps of different sizes and hung at different lengths can create an unlimited number of lighting compositions in the room.

APPLICATION

The lamp is dedicated for indoor use. It is used as a source of main light in representative rooms, hotels, restaurants, conference rooms. Unique design and energy-saving LED modules also dedicate the lamp for use in modern office buildings.

BARIS SQUARE 40 LED Z 1162X1162MM 15475LM PLX I CL. IP20 830 116W BLACK

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	938955	Diffuser type:	OPAL
EAN:	5905963938955	Diffuser colour:	milky
Light source:	LED module	Material of the body:	aluminium
Rated power of the luminaire [W]:	116	Colour of the body:	black
Luminous flux [lm]:	15475	Dimensions (H/W/T/S) [mm]:	1162/1162/52
Supply voltage [V]:	220-240	Mounting dimensions [mm]:	260/70
Frequency [Hz]:	50-60	Impact resistance:	IK06
Luminous efficacy [lm/W]:	133	Ingress protection:	IP20
Energy efficiency class:	D	Mounting version:	suspended
Electrical protection class:	I	Working temperature [°C]:	from -25 to +35
Colour temperature [K]:	3000	Category type:	decorative fixtures
Color rendering index (Ra) >:	80	Category of application:	office lighting
SDCM:	3	Warranty [years]:	5
LED lifespan L70B50 [h]:	150000	CE certificate:	21/2023
LED lifespan L80B20 [h]:	100000	Manual:	Download PDF
LED lifespan L90B10 [h]:	50000	Environmental Product Declaration (EPD):	852/2025
Light distribution type:	open space	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Surge protection [kV]:	1	Plik LDT:	Download
Diffuser material:	PC		

Card creation date: 17 February 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).  Certificate CE - Nr: 21/2023