BARIS SQUARE 40 LED Z 602X602MM 5300LM PRM DALI I KL. IP20 830 56W BLACK

DETAILED CARD



TECHNICAL PARAMETERS

Light source:	LED module
Rated power of the luminaire [W]*:	56
Luminous flux [lm]*:	5300
Energy efficiency class:	F
Electrical protection class:	I
Impact resistance:	IK06
Ingress protection:	IP20
Colour temperature [K]:	3000
Diffuser colour:	prismatic
Colour of the body:	black

CHARACTERISTICS

Baris Square 40 Led is a striking pendant lamp. Its classic shape fits perfectly into modern design. The lamp body is made of anodized aluminum profile in gray or aluminum profile painted in white or black (other colors available on request). The lamp is offered with two types of lampshade - prismatic or milky. The availability of the lamp in three sizes allows you to design the distribution of lighting in an individually tailored way. Lamps of different sizes and hung at different lengths can create an unlimited number of lighting compositions in the room.

APPLICATION

The lamp is dedicated for indoor use. It is used as a source of main light in representative rooms, hotels, restaurants, conference rooms. Unique design and energy-saving LED modules also dedicate the lamp for use in modern office buildings.

BARIS SQUARE 40 LED Z 602X602MM 5300LM PRM DALI I KL. IP20 830 56W BLACK

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	938344	**Light distribution type:**	open space
EAN:	5905963938344	**Surge protection [kV]:**	1
Light source:	LED module	**Diffuser material:**	PC
Rated power of the luminaire [W]:	56	**Diffuser type:**	clear
Luminous flux [lm]:	5300	**Diffuser colour:**	prismatic
Supply voltage [V]:	220-240	**Material of the body:**	aluminium
Frequency [Hz]:	50-60	**Colour of the body:**	black
Luminous efficacy [lm/W]:	97	**Dimensions (H/W/T/S) [mm]:**	602/602/52
Energy efficiency class:	F	**Mounting dimensions [mm]:**	160/40
Electrical protection class:	I	**Impact resistance:**	IK06
Colour temperature [K]:	3000	**Ingress protection:**	IP20
Colour rendering index:	>80	**Mounting version:**	suspended
SDCM:	≤ 3	**Working temperature [°C]:**	from -25 to +35
LED lifespan L70B50 [h]:	111500	**Warranty [years]:**	5
LED lifespan L80B20 [h]:	70400	**CE certificate:**	211/2023
LED lifespan L90B10 [h]:	34000		

Card creation date: 31 August 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 211/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl