

BARIS SQUARE 40 LED Z 882X882MM 8750LM PLX I KL. IP20 840 86W GRAY RAL9006

DETAILED CARD



TECHNICAL PARAMETERS

Light source:	LED module
Rated power of the luminaire [W]*:	86
Luminous flux [lm]*:	8750
Energy efficiency class:	E
Electrical protection class:	I
Impact resistance:	IK06
Ingress protection:	IP20
Colour temperature [K]:	4000
Diffuser colour:	milky
Colour of the body:	grey

CHARACTERISTICS

Baris Square 40 Led is a striking pendant lamp. Its classic shape fits perfectly into modern design. The lamp body is made of anodized aluminum profile in gray or aluminum profile painted in white or black (other colors available on request). The lamp is offered with two types of lampshade - prismatic or milky. The availability of the lamp in three sizes allows you to design the distribution of lighting in an individually tailored way. Lamps of different sizes and hung at different lengths can create an unlimited number of lighting compositions in the room.

APPLICATION

The lamp is dedicated for indoor use. It is used as a source of main light in representative rooms, hotels, restaurants, conference rooms. Unique design and energy-saving LED modules also dedicate the lamp for use in modern office buildings.

BARIS SQUARE 40 LED Z 882X882MM 8750LM PLX I KL. IP20 840 86W GRAY RAL9006

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	939334	Surge protection [kV]:	1
EAN:	5905963939334	Diffuser material:	PC
Light source:	LED module	Diffuser type:	OPAL
Rated power of the luminaire [W]:	86	Diffuser colour:	milky
Luminous flux [lm]:	8750	Material of the body:	aluminium
Supply voltage [V]:	220-240	Colour of the body:	grey
Frequency [Hz]:	50-60	Dimensions (H/W/T/S) [mm]:	882/882/52
Luminous efficacy [lm/W]:	102	Mounting dimensions [mm]:	160/40
Energy efficiency class:	E	Impact resistance:	IK06
Electrical protection class:	I	Ingress protection:	IP20
Colour temperature [K]:	4000	Mounting version:	suspended
Colour rendering index:	80	Working temperature [°C]:	from -25 to +35
SDCM:	≤ 3	Warranty [years]:	5
LED lifespan L70B50 [h]:	111500	CE certificate:	211/2023
LED lifespan L80B20 [h]:	70400	Category type:	decorative fixtures
LED lifespan L90B10 [h]:	34000	Plik LDT:	Download
Light distribution type:	open space		

Card creation date: 03 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 211/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl