

# TYTAN 2 LED CLUE IOT BT 1150MM 4150LM 830 IP66 RCR 28W

DETAILED CARD



## TECHNICAL PARAMETERS

Light source:	LED module
Nominal power [W]:	28
Ingress protection:	IP66
Impact resistance:	IK09
Luminous flux [lm]*:	4150
Colour temperature [K]:	3000
Electrical protection class:	I
Energy efficiency class:	C
Material of the body:	PC
Colour of the body:	grey

## CHARACTERISTICS

TYTAN 2 LED IoT is a lamp that represents a new generation of lamps dedicated to LED technology. Designed from scratch, it introduces new solutions to improve light distribution and temperature balance. Diodes from a renowned manufacturer and new LED modules contribute to a very high luminous efficiency: 155 lm/W. This guarantees the achievement of the required level of illumination and energy savings of up to 68%. The lamp uses the solution of integrating the lampshade with the LED module. The IoT version of this lamp is ready to work independently without an external control system. Integrated Bluetooth modules or an infrared receiver allow remote communication and adjust the lamp's operation as desired. In addition, we offer a light and motion sensor which will further reduce lighting energy consumption. The lamp has a number of improvements to make installation easier and faster: a shade hanging system, adjustable brackets that provide a mounting tolerance of +/-50 mm. It comes standard with durable stainless steel (INOX) clips. The lamp body and lampshade are UV resistant. Warranty up to 5 years.

## APPLICATION

Multifunctional LED lamp is designed for use in areas with high requirements for dustproof and waterproof. Particularly recommended for illuminating public facilities including educational and educational hospital facilities, halls, garages, passageways, warehouses, stores, food industry and food commodity-related commercial and service facilities, industrial facilities (factories, laboratories), warehouses, parking lots (underground and multi-level), sports stadiums, transport terminals and underground passageways. TYTAN 2 LED IoT will work especially well in facilities with access to sunlight by reducing the energy required for lighting. Thanks to the built-in motion sensor, the lamp will also be ideal in places where the light can only burn when a person is present. The lamp is ideal for new lighting applications, as well as replacing traditional fluorescent fixtures with energy-efficient LED solutions. Its design is suitable for surface and pendant mounting.

# TYTAN 2 LED CLUE IOT BT 1150MM 4150LM 830 IP66 RCR 28W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Nominal power [W]:	28	Diffuser material:	PC
Index:	680663	Diffuser type:	MAT
EAN:	5905963680663	Colour of the body:	grey
Colour temperature [K]:	3000	Dimensions (H/W/T/S) [mm]:	1152/85/80
Light source:	LED module	Mounting dimensions [mm]:	800
Luminous flux [lm]:	4150	Impact resistance:	IK09
Supply voltage [V]:	220-240	Ingress protection:	IP66
Frequency [Hz]:	50-60	Mounting version:	surface, suspended
Luminous efficacy [lm/W]:	140	Working temperature [°C]:	from -20 to +35
Energy efficiency class:	C	Motion sensor:	yes
Electrical protection class:	I	Number on the palette [pcs]:	100
Colour rendering index:	>80	Warranty [years]:	5
SDCM:	≤ 3	Manual:	<a href="#">Download PDF</a>
LED lifespan L70B50 [h]:	109000	CE certificate:	<a href="#">443/2023</a>
LED lifespan L80B20 [h]:	69000	Photobiological safety:	RG0 - exempt (no photobiological hazard)
LED lifespan L90B10 [h]:	34000		
Beam angle [°]:	120		
Exchangeable source:	yes		

Card creation date: 10 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 443/2023