

# TYTAN 2 LED IOT RC PIR HYT 1260MM 2450LM 830 IP65 (16W)

DETAILED CARD



## TECHNICAL PARAMETERS

Light source:	LED module
Nominal power [W]:	16
Ingress protection:	IP66
Impact resistance:	IK09
Luminous flux [lm]*:	2450
Colour temperature [K]:	3000
Electrical protection class:	I
Energy efficiency class:	C
Material of the body:	PC
Colour of the body:	grey

## CHARACTERISTICS

Tytan 2 LED IoT - smart industrial lamp. The innovative Tytan 2 LED IoT lamp is an advanced lighting solution that combines the latest LED technology with intelligent control functions. Designed for maximum efficiency. Key benefits: exceptional luminous efficacy: 155 lm/W, energy savings of up to 68%, integrated diffuser with LED module, warranty of up to 5 years, UV-resistant design, easy installation with +/-50 mm adjustment, high-quality stainless steel (INOX) clips. **IoT characteristics** The **IoT RC PIR HYT** version has: **PIR** motion and daylight sensor programmable by **RC** remote control and **ON/OFF** driver without dimming function of the light source. Each version of the lamp can operate autonomously without an external control system, providing the flexibility to adapt the lighting to individual needs. Integrated communication modules enable remote management of operating parameters, while optional motion and light sensors further optimise energy consumption.

## APPLICATION

Multifunctional LED lamp is designed for use in areas with high requirements for dustproof and waterproof. Particularly recommended for illuminating public facilities including educational and educational hospital facilities, halls, garages, passageways, warehouses, stores, food industry and food commodity-related commercial and service facilities, industrial facilities (factories, laboratories), warehouses, parking lots (underground and multi-level), sports stadiums, transport terminals and underground passageways. TYTAN 2 LED IoT will work especially well in facilities with access to sunlight by reducing the energy required for lighting. Thanks to the built-in motion sensor, the lamp will also be ideal in places where the light can only burn when a person is present. The lamp is ideal for new lighting applications, as well as replacing traditional fluorescent fixtures with energy-efficient LED solutions. Its design is suitable for surface and pendant mounting.

# TYTAN 2 LED IOT RC PIR HYT 1260MM 2450LM 830 IP65 (16W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	680427	<b>Diffuser material:</b>	PC
<b>EAN:</b>	5905963680427	<b>Diffuser type:</b>	matt
<b>Light source:</b>	LED module	<b>Colour of the body:</b>	grey
<b>Nominal power [W]:</b>	16	<b>Dimensions (H/W/T/S) [mm]:</b>	1259/85/80
<b>Luminous flux [lm]:</b>	2450	<b>Mounting dimensions [mm]:</b>	800
<b>Supply voltage [V]:</b>	220-240	<b>Impact resistance:</b>	IK09
<b>Frequency [Hz]:</b>	50-60	<b>Ingress protection:</b>	IP66
<b>Luminous efficacy [lm/W]:</b>	144	<b>Mounting version:</b>	surface, suspended
<b>Energy efficiency class:</b>	C	<b>Working temperature [°C]:</b>	from -20 to +35
<b>Electrical protection class:</b>	I	<b>PIR:</b>	yes
<b>Colour temperature [K]:</b>	3000	<b>Version:</b>	RC PIR HYT
<b>Color rendering index (Ra) &gt;:</b>	80	<b>Number on the palette [pcs]:</b>	100
<b>SDCM:</b>	3	<b>Warranty [years]:</b>	5
<b>LED lifespan L70B50 [h]:</b>	116000	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>LED lifespan L80B20 [h]:</b>	73000	<b>CE certificate:</b>	<a href="#">443/2023</a>
<b>LED lifespan L90B10 [h]:</b>	35000	<b>Photobiological safety:</b>	RG0 - exempt (no photobiological hazard)
<b>Beam angle [°]:</b>	120	<b>HACCP:</b>	<a href="#">852/2004</a>
<b>Exchangeable source:</b>	yes		

Card creation date: 18 July 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 443/2023