

TYTAN 2 LED CLUE IOT PIR RC 1260MM 2650LM 840 IP65 16W

DETAILED CARD



TECHNICAL PARAMETERS

Light source:	LED module
Nominal power [W]:	16
Ingress protection:	IP66
Impact resistance:	IK09
Luminous flux [lm]*:	2650
Colour temperature [K]:	4000
Electrical protection class:	I
Energy efficiency class:	C
Material of the body:	PC
Colour of the body:	grey

CHARACTERISTICS

TYTAN 2 LED IoT is a lamp that represents a new generation of lamps dedicated to LED technology. Designed from scratch, it introduces new solutions to improve light distribution and temperature balance. Diodes from a renowned manufacturer and new LED modules contribute to a very high luminous efficiency: 155 lm/W. This guarantees the achievement of the required level of illumination and energy savings of up to 68%. The lamp uses the solution of integrating the lampshade with the LED module. The IoT version of this lamp is ready to work independently without an external control system. Integrated Bluetooth modules or an infrared receiver allow remote communication and adjust the lamp's operation as desired. In addition, we offer a light and motion sensor which will further reduce lighting energy consumption. The lamp has a number of improvements to make installation easier and faster: a shade hanging system, adjustable brackets that provide a mounting tolerance of +/-50 mm. It comes standard with durable stainless steel (INOX) clips. The lamp body and lampshade are UV resistant. Warranty up to 5 years.

APPLICATION

Multifunctional LED lamp is designed for use in areas with high requirements for dustproof and waterproof. Particularly recommended for illuminating public facilities including educational and educational hospital facilities, halls, garages, passageways, warehouses, stores, food industry and food commodity-related commercial and service facilities, industrial facilities (factories, laboratories), warehouses, parking lots (underground and multi-level), sports stadiums, transport terminals and underground passageways. TYTAN 2 LED IoT will work especially well in facilities with access to sunlight by reducing the energy required for lighting. Thanks to the built-in motion sensor, the lamp will also be ideal in places where the light can only burn when a person is present. The lamp is ideal for new lighting applications, as well as replacing traditional fluorescent fixtures with energy-efficient LED solutions. Its design is suitable for surface and pendant mounting.

TYTAN 2 LED CLUE IOT PIR RC 1260MM 2650LM 840 IP65 16W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	680434	Beam angle [°]:	120
EAN:	5905963680434	Exchangeable source:	yes
Light source:	LED module	Diffuser material:	PC
Nominal power [W]:	16	Diffuser type:	MAT
Luminous flux [lm]:	2650	Colour of the body:	grey
Supply voltage [V]:	220-240	Dimensions (H/W/T/S) [mm]:	1259/85/80
Frequency [Hz]:	50-60	Mounting dimensions [mm]:	800
Luminous efficacy [lm/W]:	156	Impact resistance:	IK09
Energy efficiency class:	C	Ingress protection:	IP66
Electrical protection class:	I	Mounting version:	surface, suspended
Colour temperature [K]:	4000	Working temperature [°C]:	from -20 to +35
Colour rendering index:	>80	PIR:	yes
SDCM:	≤ 3	Warranty [years]:	5
LED lifespan L70B50 [h]:	116000	CE certificate:	443/2023
LED lifespan L80B20 [h]:	73000	Manual:	Download PDF
LED lifespan L90B10 [h]:	35000	Photobiological safety:	RG0 - exempt (no photobiological hazard)

Card creation date: 19 August 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 443/2023