

TYTAN 2 LED IOT RC PIR HYT 1260MM 7850LM 840 IP65 (47W)

DETAILED CARD



TECHNICAL PARAMETERS

Light source:	LED module
Nominal power [W]:	47
Ingress protection:	IP66
Impact resistance:	IK09
Luminous flux [lm]*:	7850
Colour temperature [K]:	4000
Electrical protection class:	I
Energy efficiency class:	C
Material of the body:	PC
Colour of the body:	grey

CHARACTERISTICS

Tytan 2 LED IoT - smart industrial lamp. The innovative Tytan 2 LED IoT lamp is an advanced lighting solution that combines the latest LED technology with intelligent control functions. Designed for maximum efficiency. Key benefits: exceptional luminous efficacy: 155 lm/W, energy savings of up to 68%, integrated diffuser with LED module, warranty of up to 5 years, UV-resistant design, easy installation with +/-50 mm adjustment, high-quality stainless steel (INOX) clips. **IoT characteristics** The **IoT RC PIR HYT** version has: **PIR** motion and daylight sensor programmable by **RC** remote control and **ON/OFF** driver without dimming function of the light source. Each version of the lamp can operate autonomously without an external control system, providing the flexibility to adapt the lighting to individual needs. Integrated communication modules enable remote management of operating parameters, while optional motion and light sensors further optimise energy consumption.

APPLICATION

Multifunctional LED lamp is designed for use in areas with high requirements for dustproof and waterproof. Particularly recommended for illuminating public facilities including educational and educational hospital facilities, halls, garages, passageways, warehouses, stores, food industry and food commodity-related commercial and service facilities, industrial facilities (factories, laboratories), warehouses, parking lots (underground and multi-level), sports stadiums, transport terminals and underground passageways. TYTAN 2 LED IoT will work especially well in facilities with access to sunlight by reducing the energy required for lighting. Thanks to the built-in motion sensor, the lamp will also be ideal in places where the light can only burn when a person is present. The lamp is ideal for new lighting applications, as well as replacing traditional fluorescent fixtures with energy-efficient LED solutions. Its design is suitable for surface and pendant mounting.

TYTAN 2 LED IOT RC PIR HYT 1260MM 7850LM 840 IP65 (47W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	680557	Diffuser material:	PC
EAN:	5905963680557	Diffuser type:	matt
Light source:	LED module	Colour of the body:	grey
Nominal power [W]:	47	Dimensions (H/W/T/S) [mm]:	1259/85/80
Luminous flux [lm]:	7850	Mounting dimensions [mm]:	800
Supply voltage [V]:	220-240	Impact resistance:	IK09
Frequency [Hz]:	50-60	Ingress protection:	IP66
Luminous efficacy [lm/W]:	155	Mounting version:	surface, suspended
Energy efficiency class:	C	Working temperature [°C]:	from -20 to +35
Electrical protection class:	I	PIR:	yes
Colour temperature [K]:	4000	Version:	RC PIR HYT
Colour rendering index:	80	Number on the palette [pcs]:	100
SDCM:	≤ 3	Warranty [years]:	5
LED lifespan L70B50 [h]:	109000	Manual:	Download PDF
LED lifespan L80B20 [h]:	69000	CE certificate:	443/2023
LED lifespan L90B10 [h]:	34000	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Beam angle [°]:	120	HACCP:	852/2004
Exchangeable source:	yes		

Card creation date:18 July 2025
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric andelectronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 443/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl