

TYTAN 2 LED IOT RC PIR HYT 1260MM 9050LM 850 IP65 (55W)

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|------------------------------|------------|
| Light source: | LED module |
| Nominal power [W]: | 55 |
| Ingress protection: | IP66 |
| Impact resistance: | IK09 |
| Luminous flux [lm]*: | 9050 |
| Colour temperature [K]: | 5000 |
| Electrical protection class: | I |
| Energy efficiency class: | C |
| Material of the body: | PC |
| Colour of the body: | grey |

CHARACTERISTICS

Tytan 2 LED IoT - smart industrial lamp. The innovative Tytan 2 LED IoT lamp is an advanced lighting solution that combines the latest LED technology with intelligent control functions. Designed for maximum efficiency. Key benefits: exceptional luminous efficacy: 155 lm/W, energy savings of up to 68%, integrated diffuser with LED module, warranty of up to 5 years, UV-resistant design, easy installation with +/-50 mm adjustment, high-quality stainless steel (INOX) clips. **IoT characteristics** The **IoT RC PIR HYT** version has: **PIR** motion and daylight sensor programmable by **RC** remote control and **ON/OFF** driver without dimming function of the light source. Each version of the lamp can operate autonomously without an external control system, providing the flexibility to adapt the lighting to individual needs. Integrated communication modules enable remote management of operating parameters, while optional motion and light sensors further optimise energy consumption.

APPLICATION

Multifunctional LED lamp is designed for use in areas with high requirements for dustproof and waterproof. Particularly recommended for illuminating public facilities including educational and educational hospital facilities, halls, garages, passageways, warehouses, stores, food industry and food commodity-related commercial and service facilities, industrial facilities (factories, laboratories), warehouses, parking lots (underground and multi-level), sports stadiums, transport terminals and underground passageways. TYTAN 2 LED IoT will work especially well in facilities with access to sunlight by reducing the energy required for lighting. Thanks to the built-in motion sensor, the lamp will also be ideal in places where the light can only burn when a person is present. The lamp is ideal for new lighting applications, as well as replacing traditional fluorescent fixtures with energy-efficient LED solutions. Its design is suitable for surface and pendant mounting.

TYTAN 2 LED IOT RC PIR HYT 1260MM 9050LM 850 IP65 (55W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|---|---------------|---|---|
| Index: | 680595 | Diffuser type: | matt |
| EAN: | 5905963680595 | Colour of the body: | grey |
| Light source: | LED module | Dimensions (H/W/T/S) [mm]: | 1259/85/80 |
| Nominal power [W]: | 55 | Mounting dimensions [mm]: | 800 |
| Luminous flux [lm]: | 9050 | Impact resistance: | IK09 |
| Supply voltage [V]: | 220-240 | Ingress protection: | IP66 |
| Frequency [Hz]: | 50-60 | Mounting version: | surface, suspended |
| Luminous efficacy [lm/W]: | 153 | Working temperature [°C]: | from -20 to +35 |
| Energy efficiency class: | C | PIR: | yes |
| Electrical protection class: | I | Version: | RC PIR HYT |
| Colour temperature [K]: | 5000 | Number on the palette [pcs]: | 100 |
| Color rendering index (Ra) >: | 80 | Photobiological safety: | RG0 - exempt (no photobiological hazard) |
| SDCM: | 3 | Warranty [years]: | 5 |
| LED lifespan L70B50 [h]: | 109000 | CE certificate: | 443/2023 |
| LED lifespan L80B10 [h]: | 69000 | HACCP: | 852/2004 |
| LED lifespan L90B10 [h]: | 34000 | PZH certificate: | B-BK-60112-0280/2025 |
| Beam angle [°]: | 120 | Environmental Product Declaration (EPD): | 944/2026 |
| Exchangeable source: | yes | Manual: | Download PDF |
| Diffuser material: | PC | ISO Certificates: | 9001:2015, 14001:2015, 45001:2018, 50001:2018 |

Card creation date: 04 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 443/2023