DETAILED CARD





TECHNICAL PARAMETERS

Light source:	LED module	
Ingress protection:	IP20	
Nominal power [W]:	8	
Luminous flux [lm]*:	900	
Colour temperature [K]:	4000	
Colour rendering index:	>80	
SDCM:	≤ 3	
Energy efficiency class:	E	
Diffuser material:	PMMA	
Diffuser type:	OPAL	

CHARACTERISTICS

Robust frame made of aluminum profile with a very narrow cross profile. The special features of the Smart Led Evo Bracket line include discreet elegance and energy efficiency. The optical system involves an iridescent screen that provides soft light.

The luminaire is available in:

- 3 lengths and 6 powers,

- 2 structural variants: with an additional spacer profile (variant B) or without it (variant A) $\!\!\!\!$

- 2 lighting versions: one-sided (DIR) or double-sided (DIR/IND).

APPLICATION

Unique design predisposes these luminaires for the following environments: offices, conference rooms and other representative spaces.



DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Dimensions (H/W/T/S) [mm]:	298/55/70
Nominal power [W]:	8	Mounting dimensions [mm]:	200
Rated power of the luminaire [W]:	9.50	Ingress protection:	IP20
Supply voltage [V]:	220-240	Mounting version:	surface
Frequency [Hz]:	50 - 60	Working temperature [°C]:	from 0 to +25
Luminous flux [Im]:	900	Net weight [kg]:	0.800
Luminous efficacy [lm/W]:	94	Index:	656002
Energy efficiency class:	E	EAN:	5905963656002
Electrical protection class:	1	Category type:	battens
Colour temperature [K]:	4000	Version:	А
Colour rendering index:	>80	CE certificate:	<u>52/2018</u>
SDCM:	≤ 3	Light distribution type:	DIR
Beam angle [°]:	DIR	ETIM class:	EC002892
Diffuser material:	РММА	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral
Diffuser type:	OPAL		limitation)
Material of the body:	aluminium	Warranty [years]:	5
Colour of the body:	C0 anode	Manual:	Download PDF

Card creation date: 12 April 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

Certificate CE - Nr: 52/2018

This product

This product is a subject to electric and electronic waste equipment regulations (WEEE).

