UV-C STERILON MAX PRO 1200

DETAILED CARD



TECHNICAL PARAMETERS

Index:	250026
Nominal power [W]:	360
Supply voltage [V]:	220 - 240
Electrical protection class:	I
Material of the body:	Steel
Ingress protection:	IP20
Dimensions (H/W/T/S) [mm]:	1895/650/650

CHARACTERISTICS

Flow luminaires emitting ultraviolet (UV-C) light are one of the most effective devices capable of removing viruses, bacteria, mold from the surface or destroying the DNA or RNA of any exposed microorganisms. • Air-flow disinfection function• Steel body, powder-coated in white-graphite • Possibility to reset the operating time counter• The luminaire is equipped with a LED operating time counter used for indicating the consumption of UV-C fluorescent lamps• Very quiet operation 37dB* • CO2 sensor• Temperature measurement• Humidity measurement

APPLICATION

Luminaires are recommended for use in large service-providing facilities (hair and beauty salons), health care facilities, hotels, restaurants, public administration, educational and care facilities.

* Parameters may vary (+/- 10%)

UV-C STERILON MAX PRO 1200

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	250026	**Total power consumption [W]:**	360
Light source:	UV-C	**UV-C wavelength [nm]:**	253.70
Nominal power [W]:	360	**Dust filter:**	yes
Supply voltage [V]:	220 - 240	**Flow air disinfection function:**	yes
Electrical protection class:	I	**Working time counter:**	yes
Exchangeable source:	yes	**HEPA filter holder:**	yes
Material of the body:	Steel	**Air flow [m3 / h]:**	1200
Colour of the body:	white-graphite	**Type of light:**	ultraviolet UV-C
Dimensions (H/W/T/S) [mm]:	1895/650/650	**Protection against opening:**	yes
Ingress protection:	IP20	**Service life of the UV-C radiation source [h]:**	9000
Plug type:	UNI-SCHUKO	**Noise intensity [dB]:**	37
Cable length [m]:	4	**Internal element emitting UV-C radiation [W]:**	10x36
Switch:	yes	**CE certificate:**	369/2023
Net weight [kg]:	85	**Manual:**	Download PDF

TECHNICAL DETAILS



Panel max pro



CO2 sensor - Sterilon Max Pro

UV-C STERILON MAX PRO 1200

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
249778	HEPA filter for UV-C STERILON MAX 800/1200/1500
249785	Carbon filter for UV-STERILON MAX 800/1200/1500
249822	Pre-filter for UV-STERILON MAX 800/1200/1500

Card creation date: 15 December 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 369/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl