



TECHNICAL PARAMETERS

Light source:	moduł LED
Ingress protection:	IP20
Nominal power [W]:	8
Luminous flux [lm]*:	850 - 4900
Colour temperature [K]:	3000; 4000
Colour rendering index:	>80
SDCM:	≤ 3
Energy efficiency class:	D; E; F; G
Diffuser material:	PC; PMMA
Diffuser type:	OPAL

CHARACTERISTICS

Robust frame made of aluminum profile with a very narrow cross profile. The special features of the Smart Led Evo Bracket line include discreet elegance and energy efficiency. The optical system involves an iridescent screen that provides soft light.

The luminaire is available in:

- 3 lengths and 6 powers,
- 2 structural variants: with an additional spacer profile (variant B) or without it (variant A)
- 2 lighting versions: one-sided (DIR) or double-sided (DIR/IND).

APPLICATION

Unique design predisposes these luminaires for the following environments: offices, conference rooms and other representative spaces.

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	moduł LED	Colour of the body:	anoda CO
Nominal power [W]:	8	Dimensions (H/W/T/S) [mm]:	1138/125/70; 1138/55/70; 298/125/70; 298/55/70; 578/125/70; 578/55/70; 600/40/55
Rated power of the luminaire [W]:	9.50; 18.70; 20.00; 30.70; 49.00	Mounting dimensions [mm]:	max 720
Supply voltage [V]:	220-240	Ingress protection:	IP20
Frequency [Hz]:	50-60	Mounting version:	natynkowy; natynkowy, naścienny
Luminous flux [lm]:	850 - 4900	Working temperature [°C]:	od 0 do +25
Luminous efficacy [lm/W]:	72	Index:	x
Energy efficiency class:	D; E; F; G	EAN:	x
Electrical protection class:	I	Category type:	battens
Colour temperature [K]:	3000; 4000	Version:	A; B
Colour rendering index:	>80	CE certificate:	52/2018; 53/2018
SDCM:	≤ 3	Light distribution type:	DIR; DIR/IND
Beam angle [°]:	DIR; DIR/IND	ETIM class:	EC002892
Diffuser material:	PC; PMMA	Photobiological safety:	grupa ryzyka 1 (niskie ryzyko)
Diffuser type:	OPAL	Warranty [years]:	5
Material of the body:	aluminium	Manual:	Download PDF

Card creation date: 11 April 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 53/2018



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl