

INDUSTRY SLIM LED ENDURA 50°C 1177MM 11400LM 840 IP66 120D DALI (69W)

DETAILED CARD



TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	50
Luminous flux [lm]*:	max 11600
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50-60
Energy efficiency class:	B; C
Electrical protection class:	I
Colour temperature [K]:	4000; 5000

CHARACTERISTICS

Industry Slim Led Endura - sealed aluminum luminaire characterized by high luminous flux and very high luminous efficiency >160 lm/W, which makes this luminaire highly energy-efficient and environmentally friendly. It is distinguished by a large operating temperature range of -40° to +60° (+50° version also available) Celsius as well as very high IP66 tightness. It owes this tightness to its well-thought-out design. The polycarbonate diffuser is permanently attached to the housing with a heavy-duty silicone gasket. This means that in addition to the tightness thus achieved, the light module is protected from uncontrolled interference and access to the LEDs. The tightness of the lamp, is ensured by the gland, which screwed tightens the gasket and prevents the penetration of dust or moisture and water. Industry Slim Led allows for pendant or surface mounting.

APPLICATION

The luminaire is designed to illuminate industrial and warehouse facilities, due to its minimal size also in hard-to-reach areas. The Industry Slim Led luminaire is available in various versions: with different optics, wide distribution, narrow distribution and dedicated for high storage warehouses and five types of diffuser, including anti-glare diffuser.

INDUSTRY SLIM LED ENDURA 50°C 1177MM 11400LM 840 IP66 120D DALI (69W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	x	Diffuser material:	PC
EAN:	x	Optics material:	PC
Light source:	moduł LED	Material of the body:	aluminium
Rated power of the luminaire [W]:	50	Colour of the body:	szary
Luminous flux [lm]:	max 11600	Dimensions (H/W/T/S) [mm]:	1177/50/75; 621/50/75
Supply voltage [V]:	220 - 240	Mounting dimensions [mm]:	800
Frequency [Hz]:	50-60	Impact resistance:	IK09
Luminous efficacy [lm/W]:	151	Ingress protection:	IP66
Energy efficiency class:	B; C	Mounting version:	Natynk/Zwieszany
Electrical protection class:	I	Working temperature [°C]:	od -40 do +50; od -40 do +60
Colour temperature [K]:	4000; 5000	DIMM DALI:	yes
SDCM:	≤ 3	Wire type:	LS2; LS2,5
LED lifespan L70B50 [h]:	179000	Through wiring:	2x1,5; 2x2,5
LED lifespan L80B20 [h]:	112000	Warranty [years]:	5
LED lifespan L90B10 [h]:	54000	CE certificate:	110/2022; 163/2023
Beam angle [°]:	40x30; 46x117; 105; 120	Manual:	Pobierz PDF

Card creation date: 22 September 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 163/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl