

MAGNUM FUTURE 105W I PROTECTION CLASS WITH DK SOCKETS

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP54
Impact resistance:	IK10
Rated power of the luminaire [W]*:	105
Colour temperature [K]:	4000
Luminous flux [lm]*:	14055
Supply voltage [V]:	220-240
Energy efficiency class:	D
Electrical protection class:	I
Colour of the body:	grey
Diffuser material:	PC

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polipropylene (PP). Anti-glare diffuser made of polycarbonat (PC) which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

A rubber cable H07RN-F 3x1,5 mm² (5 m) comes as standard.

APPLICATION

With a variety of functions, the lamp is ideal for illuminating any workplace. The high luminous flux and maximum degree of impact resistance are especially important for lighting construction sites or for the work of services intervening in various emergencies. A high degree of waterproofness allows its use in the harshest weather conditions. The multi-position arm and numerous accessories provide a wide range of mounting options so as to precisely direct the light beam, leaving the worker's hands free. Its small size and light weight make it easy to use in workshops, car showrooms, to illuminate the workplace in industrial halls or finishing work.

MAGNUM FUTURE 105W I PROTECTION CLASS WITH DK SOCKETS

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	244537	Colour rendering index:	>80
Rated power of the luminaire [W]:	105	Diffuser material:	PC
EAN:	5905963244537	Diffuser colour:	white
Colour temperature [K]:	4000	Colour of the body:	grey
Light source:	LED module	Dimensions (H/W/T/S) [mm]:	300/480/75
Luminous flux [lm]:	14055	Impact resistance:	IK10
Diffuser type:	MAT	Ingress protection:	IP54
Plug type:	UNI-SCHUKO	Sockets:	2
Socket type:	DK	Wire type:	H07RN-3x1.5mm ²
Supply voltage [V]:	220-240	Cable length [m]:	5
Frequency [Hz]:	50-60	Net weight [kg]:	3.600
Luminous efficacy [lm/W]:	134	Category type:	workplace floodlights
Energy efficiency class:	D	Manual:	Download PDF
Electrical protection class:	I	CE certificate:	122/2023

Card creation date: 13 March 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 122/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl