

# INDUSTRY SLIM LED 1177MM 14400LM 840 IP66 46X117D (94W)

---

DETAILED CARD



# INDUSTRY SLIM LED 1177MM 14400LM 840 IP66 46X117D (94W)

DETAILED CARD

## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP66
<b>Rated power of the luminaire [W]*:</b>	94
<b>Luminous flux [lm]*:</b>	14400
<b>Colour temperature [K]:</b>	4000
<b>Material of the body:</b>	aluminium
<b>Colour of the body:</b>	grey
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	clear
<b>Optics material:</b>	PC
<b>Mounting version:</b>	surface, suspended

## CHARACTERISTICS

Industry Slim Led - a brand new industrial luminaire is characterized by high luminous flux and very high luminous efficiency >160 lm/W, which makes this luminaire highly energy-efficient and environmentally friendly. It is distinguished by its very high IP66 tightness. It owes this tightness to its well-thought-out design. The polycarbonate diffuser is permanently attached to the housing with a durable silicone gasket. This means that in addition to the tightness thus achieved, the light module is protected from uncontrolled interference and access to the LEDs. The tightness of the lamp, is ensured by the gland, which screwed tightens the gasket and prevents the penetration of dust or moisture and water. Industry Slim Led allows for pendant or surface mounting.

## APPLICATION

The luminaire is designed to illuminate industrial and warehouse facilities, due to its minimal dimensions, also in hard-to-reach places. The Industry Slim Led luminaire is available in various versions: with different optics, wide, narrow, and dedicated to high-bay light distribution, and five types of the diffuser, including an anti-glare diffuser.

## DETAILS



# INDUSTRY SLIM LED 1177MM 14400LM 840 IP66 46X117D (94W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	944642	LED lifespan L90B10 [h]:	54000
Rated power of the luminaire [W]:	94	Diffuser material:	PC
EAN:	5905963944642	Optics:	46x117D
Colour temperature [K]:	4000	Optics material:	PC
Luminous flux [lm]:	14400	Material of the body:	aluminium
Supply voltage [V]:	220 - 240	Colour of the body:	grey
Beam angle [°]:	46/117	Dimensions (H/W/T/S) [mm]:	1177/50/75
Frequency [Hz]:	50-60	Ingress protection:	IP66
Light distribution type:	corridor	Impact resistance:	IK09
Luminous efficacy [lm/W]:	153	Mounting version:	surface, suspended
Energy efficiency class:	C	Working temperature [°C]:	from -25 to +35
Electrical protection class:	I	Net weight [kg]:	2.600
SDCM:	≤ 3	Warranty [years]:	5
LED lifespan L70B50 [h]:	179000	CE certificate:	<a href="#">167/2023</a>
LED lifespan L80B20 [h]:	112000	ENEC Certificate:	<a href="#">0362/ENEC/24</a>
		Manual:	<a href="#">Download PDF</a>
		Plik LDT:	

# INDUSTRY SLIM LED 1177MM 14400LM 840 IP66 46X117D (94W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
908200	TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2)
60000006	M16 stuffing box plug various PA black M-16 - BPM-21



TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) (908200)



M16 stuffing box plug various PA black M-16 - BPM-21 (60000006)

Card creation date: 05 August 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 167/2023