

# INDUSTRY SLIM LED 1177MM 16350LM 840 IP66 46X117D DALI (117W)

DETAILED CARD



# INDUSTRY SLIM LED 1177MM 16350LM 840 IP66 46X117D DALI (117W)

## DETAILED CARD

### TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP66
<b>Rated power of the luminaire [W]*:</b>	117
<b>Luminous flux [lm]*:</b>	16350
<b>Colour temperature [K]:</b>	4000
<b>Material of the body:</b>	aluminium
<b>Colour of the body:</b>	grey
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	transparent
<b>Optics material:</b>	PC
<b>Mounting version:</b>	surface, suspended

### CHARACTERISTICS

Industry Slim Led - a brand new industrial luminaire is characterized by high luminous flux and very high luminous efficiency >160 lm/W, which makes this luminaire highly energy-efficient and environmentally friendly. It is distinguished by its very high IP66 tightness. It owes this tightness to its well-thought-out design. The polycarbonate diffuser is permanently attached to the housing with a durable silicone gasket. This means that in addition to the tightness thus achieved, the light module is protected from uncontrolled interference and access to the LEDs. The tightness of the lamp, is ensured by the gland, which screwed tightens the gasket and prevents the penetration of dust or moisture and water. Industry Slim Led allows for pendant or surface mounting.

### APPLICATION

The luminaire is designed to illuminate industrial and warehouse facilities, due to its minimal dimensions, also in hard-to-reach places. The Industry Slim Led luminaire is available in various versions: with different optics, wide, narrow, and dedicated to high-bay light distribution, and five types of the diffuser, including an anti-glare diffuser.

### DETAILS




# INDUSTRY SLIM LED 1177MM 16350LM 840 IP66 46X117D DALI (117W)

## DETAILED CARD

### TECHNICAL PARAMETERS TABLE

Index:	944338	Material of the body:	aluminium
EAN:	5905963944338	Colour of the body:	grey
Rated power of the luminaire [W]:	117	Dimensions (H/W/T/S) [mm]:	1177/50/75
Luminous flux [lm]:	16350	Ingress protection:	IP66
Supply voltage [V]:	220 - 240	Impact resistance:	IK09
Frequency [Hz]:	50-60	Mounting version:	surface, suspended
Luminous efficacy [lm/W]:	140	Working temperature [°C]:	from -25 to +35
Energy efficiency class:	C	DIMM DALI:	yes
Electrical protection class:	I	The number of implement units:	2
Colour temperature [K]:	4000	Net weight [kg]:	2.280
SDCM:	3	Light distribution type:	corridor
LED lifespan L70B50 [h]:	99000	Warranty [years]:	5
LED lifespan L80B20 [h]:	63000	CE certificate:	<a href="#">167/2023</a>
LED lifespan L90B10 [h]:	31000	ENEC Certificate:	<a href="#">0362/ENEC/24</a>
Beam angle [°]:	46/117	Manual:	<a href="#">Download PDF</a>
Diffuser material:	PC	Environmental Product Declaration (EPD):	<a href="#">852/2025</a>
Optics:	46x117D	Plik LDT:	<a href="#">Download</a>
Optics material:	PC		

### LIGHT CURVES



# INDUSTRY SLIM LED 1177MM 16350LM 840 IP66 46X117D DALI (117W)

## DETAILED CARD

### ACCESSORIES AVAILABLE

index	Name
908200	TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2)
60000006	M16 stuffing box plug various PA black M-16 - BPM-21



TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) (908200)



M16 stuffing box plug various PA black M-16 - BPM-21 (60000006)

Card creation date: 16 December 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 167/2023