

BARIS 52 LED P GK 2265MM 6900LM 840 IP44/IP20 I CL. DALI PRM BLACK 64W

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP44/IP20
Rated power of the luminaire [W]*:	64
Luminous flux [lm]*:	6948
Colour temperature [K]:	4000
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	black
Diffuser material:	PC
Diffuser type:	PRM
Mounting version:	flush-mounted in plasterboard ceilings

CHARACTERISTICS

Recessed lighting luminaire of classic proportions and modern design intended for installation in plaster-cardboard ceilings. Luminaire construction allows for installation in ceilings with two-level cross grid without breaching main (top) profiles. It is possible due to appropriately selected height of the lamp profile, reduced to 37mm and separate box for the power supply, which can be placed next to the luminaire. The luminaire is offered in four lengths with the possibility to combine into a line with a constant flux ratio from the meter (system available on request). Luminaire body is made of anodized aluminum profile in grey or aluminum profile painted white or black (other colors available on request). The optical system is in the form of a dedicated, flexible opal diffuser uniformly illuminating the luminaire, with a PRM prismatic diffuser or with a louver meeting the stringent requirements regarding glare UGR<19. The luminaire comes with a complete mounting system for a quick and easy installation in plasterboard ceilings.

APPLICATION

The luminaire is dedicated for indoor use. It is applied as the source of the main light and conducive to office work requiring concentration of eyesight. Classic design, energy-saving LED modules and the possibility of cooperation with external lighting control systems in the DALI standard dedicate the lamp to be used in modern office buildings of the A+ class, with particular consideration of representative rooms, conference halls, passageways and everywhere, where a low glare and/or high IP44 sealing from below is required.

BARIS 52 LED P GK 2265MM 6900LM 840 IP44/IP20 I CL. DALI PRM BLACK 64W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	936548	Exchangeable source:	1
Rated power of the luminaire [W]:	64	Diffuser material:	PC
EAN:	5905963936548	Colour of the body:	black
Colour temperature [K]:	4000	Diffuser colour:	clear
Luminous flux [lm]:	6948	Dimensions (H/W/T/S) [mm]:	37/69/2265
Diffuser type:	PRM	Optics:	Microprism
Supply voltage [V]:	220 - 240	Material of the body:	aluminium
Frequency [Hz]:	50 - 60	Ingress protection:	IP44/IP20
Luminous efficacy [lm/W]:	107	Mounting version:	flush-mounted in plasterboard ceilings
Energy efficiency class:	E	Net weight [kg]:	2.910
Electrical protection class:	I	Impact resistance:	IK03
Colour rendering index:	>80	Working temperature [°C]:	from -25 to +35
SDCM:	≤ 3	CE certificate:	235/2023
LED lifespan L70B50 [h]:	109 000	PZH certificate:	B-BK-60112-0357/2023
LED lifespan L80B20 [h]:	69 000	Manual:	Download PDF
DIMM DALI:	1	Plik LDT:	Pobierz
LED lifespan L90B10 [h]:	34000		

Card creation date: 16 September 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 235/2023