

GIANT LED EVO GREY 45000LM WITH DANISH SOCKETS

DETAILED CARD



TECHNICAL PARAMETERS

Index:	901317
Light source:	LED module
Rated power of the luminaire [W]*:	288
Luminous flux [lm]*:	45000
Colour temperature [K]:	4000
Diffuser material:	PC
Diffuser type:	MAT
Diffuser colour:	white
Colour of the body:	grey
Dimensions (H/W/T/S) [mm]:	740/420/320

CHARACTERISTICS

Lightweight and very powerful portable LED floodlight for professional use. Provides even and stable directional illumination. The lamp is made of impact-resistant polypropylene (PP). The anti-glare diffuser made of polycarbonate (PC), despite its matte surface, transmits up to 80% of the light emitted by the LED. It has an ergonomic carrying handle. Standard: rubber cable H07RN-F 3×1.5mm² (5m). With a variety of functions, the lamp is ideal for illuminating any workplace. The high luminous flux and the maximum degree of impact resistance are particularly important in the lighting of construction sites or in the work of services intervening at various emergencies. A high degree of waterproofness allows its use in the harshest weather conditions. Its light weight makes it easy to use for workplace lighting in industrial halls or finishing work.

APPLICATION

Temporary lighting for construction site, finishing works, outdoor earthworks, road and highway repair, Especially useful for mobile services , emergency services, police, military, firefighters, construction crews, electricians, railroad repair, etc.

GIANT LED EVO GREY 45000LM WITH DANISH SOCKETS

DETAILED CARD

TECHNICAL PARAMETERS TABLE


Index:	901317	Diffuser colour:	white
EAN:	5905963901317	Colour of the body:	grey
Light source:	LED module	Dimensions (H/W/T/S) [mm]:	740/420/320
Rated power of the luminaire [W]:	288	Impact resistance:	IK10
Colour temperature [K]:	4000	Ingress protection:	IP54
Luminous flux [lm]:	45000	Plug type:	DK
Supply voltage [V]:	220-240	Socket type:	DK
Frequency [Hz]:	50-60	Sockets:	2
Luminous efficacy [lm/W]:	155.82	Wire type:	H07RN- 3x1,5mm ²
Energy efficiency class:	B	Cable length [m]:	5
Electrical protection class:	I	Net weight [kg]:	5.300
Colour rendering index:	80	Warranty [years]:	5
Diffuser material:	PC	CE certificate:	128/2023
Diffuser type:	MAT	Manual:	Download PDF

GIANT LED EVO GREY 45000LM WITH DANISH SOCKETS

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
000300	Adapter plate with click function for mounting the Giant Luminaire on the tripod
000294	Steel tripod 3 m



Steel tripod 3 m (000294)

Card creation date: 23 November 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 128/2023