

# PROFI SERVICE SET AKKU LED

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Light source:</b>	LED module
<b>Supply voltage [V]:</b>	3.7
<b>Luminous flux [lm]*:</b>	2000
<b>Electrical protection class:</b>	III
<b>Colour temperature [K]:</b>	6500
<b>Charging time [h:min]:</b>	4h
<b>Battery life [h:min]:</b>	min 1h. max 4h
<b>Battery:</b>	Li-Ion 3,7V
<b>Battery capacity [mAh]:</b>	4800
<b>Diffuser material:</b>	PC

## CHARACTERISTICS

Professional lamp used to illuminate the engine compartment. Particularly useful in servicing cars, vans and trucks. The set consists of an aluminum hood bracket (spacing from 1180mm to 1780mm) used to suspend the lamp under the hood of the repaired vehicle. The ends are covered with rubber to improve the stability of the set and further protect the hood from scratches. Battery-powered lamp allowing illumination with a flux of: 500Lm, 1000Lm, 2000Lm. The lamp also fits perfectly for illuminating the cabin of the vehicle (clamp the lamp on the side pillars of the vehicle) during cleaning repairs and detailing. The replaceable battery can be charged separately (apart from the lamp) with a C-connector.

## APPLICATION

Car services (car repairs, vans, trucks), detailing salons, car washes, mobile services, etc.

# PROFI SERVICE SET AKKU LED

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	334788	<b>Diffuser type:</b>	MAT
<b>EAN:</b>	5905963334788	<b>Diffuser colour:</b>	white
<b>Light source:</b>	LED module	<b>Colour of the body:</b>	grey
<b>Luminous flux [lm]:</b>	2000	<b>Dimensions (H/W/T/S) [mm]:</b>	1170/110
<b>Supply voltage [V]:</b>	3.7	<b>Impact resistance:</b>	IK10
<b>Colour temperature [K]:</b>	6500	<b>Ingress protection:</b>	IP20
<b>Electrical protection class:</b>	III	<b>Wire type:</b>	Tak
<b>Charging time [h:min]:</b>	4h	<b>Cable length [m]:</b>	0.50
<b>Battery:</b>	Li-Ion 3,7V	<b>Net weight [kg]:</b>	1.110
<b>Battery capacity [mAh]:</b>	4800	<b>Warranty [years]:</b>	2
<b>Battery life [h:min]:</b>	min 1h. max 4h	<b>Category type:</b>	portable fluorescent fittings
<b>Diffuser material:</b>	PC	<b>Illumination area at a distance of 1 m:</b>	2

Card creation date: 25 November 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 291/2023