

QUEST 2 LED HB M IOT RC PIR HYT DALI 14700LM I CL. IP65 850 SP10KV (108W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	695001
Rated power of the luminaire [W]*:	108
Luminous flux [lm]*:	14700
Frequency [Hz]:	50 - 60
Energy efficiency class:	C
Electrical protection class:	I
Colour temperature [K]:	5000
Beam angle [°]:	120
Light distribution type:	symmetric
Diffuser material:	glass

CHARACTERISTICS

High-quality highbay with inbuilt LED source. The body is made of die-cast aluminium, powder coated in anthracite grey (RAL 7016), and the mounting bracket is made of black-painted steel. The diffuser is made of 5 mm thick tempered glass. Available version with radio motion sensor:- allowing additional savings in electricity consumption- convenient change of parameters by remote control (to be purchased separately). **IoT characteristics IoT RC PIR HYT DALI** has **PIR** motion and light sensor programmed by **RC** remote control and **DALI** driver enabling dimming of the light source.

APPLICATION

The luminaire is dedicated for surface or suspended installation (with chains) for both internal and external use. It is designed for industrial plants, production halls and large area warehouses.

QUEST 2 LED HB M IOT RC PIR HYT DALI 14700LM I CL. IP65 850 SP10KV (108W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE


Index:	695001	Diffuser material:	glass
Light source:	LED module	Diffuser type:	transparent
Rated power of the luminaire [W]:	108	Material of the body:	aluminium
Luminous flux [lm]:	14700	Colour of the body:	anthracite grey
Supply voltage [V]:	220 - 240	Version:	RC PIR HYT DALI
Frequency [Hz]:	50 - 60	Dimensions (H/W/T/S) [mm]:	321/424/37
Luminous efficacy [lm/W]:	136	Impact resistance:	IK09
Energy efficiency class:	C	Ingress protection:	IP66
Electrical protection class:	I	Working temperature [°C]:	from -20 to +35
Colour temperature [K]:	5000	DIMM DALI:	yes
Colour rendering index:	> 80	Dimensions of single box [mm]:	450/401/80
SDCM:	≤ 3	Warranty [years]:	5
LED lifespan L70B50 [h]:	125000	CE certificate:	450/2023
LED lifespan L80B20 [h]:	79000	PZH certificate:	B-BK-60212-0480/21
LED lifespan L90B10 [h]:	38000	Environmental Product Declaration (EPD):	816/2025
Beam angle [°]:	120	Manual:	Download PDF
Light distribution type:	symmetric		
Efficiency of the luminaire:	0.89		

QUEST 2 LED HB M IOT RC PIR HYT DALI 14700LM I CL. IP65 850 SP10KV (108W)


DETAILED CARD

ACCESSORIES AVAILABLE


index	Name
699993	QUEST 2 LED M - recessed frame
699986	QUEST 2 LED L - recessed frame
699962	QUEST 2 LED L protective grid RAL7016
699979	QUEST 2 LED M protective grid RAL7016




QUEST 2 LED M - recessed frame (699993)



QUEST 2 LED L - recessed frame (699986)



QUEST 2 LED L protective grid RAL7016 (699962)



QUEST 2 LED M protective grid RAL7016 (699979)