

# QUEST 2 LED M 14700LM DALI DH I CL. IP65 850 SP10KV (108W) IOT CLUE

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	695025
Rated power of the luminaire [W]*:	108
Luminous flux [lm]*:	14700
Frequency [Hz]:	50 - 60
Energy efficiency class:	C
Electrical protection class:	I
Colour temperature [K]:	5000
Beam angle [°]:	120
Light distribution type:	symmetric
Diffuser material:	glass

## CHARACTERISTICS

High-quality highbay with inbuilt LED source. The body is made of die-cast aluminium, powder coated in anthracite grey (RAL 7016), and the mounting bracket is made of black-painted steel. The diffuser is made of 5 mm thick tempered glass.

Available version with radio motion sensor:

- allowing additional savings in electricity consumption
- convenient change of parameters by remote control (to be purchased separately).

## APPLICATION

The luminaire is dedicated for surface or suspended installation (with chains) for both internal and external use. It is designed for industrial plants, production halls and large area warehouses.

# QUEST 2 LED M 14700LM DALI DH I CL. IP65 850 SP10KV (108W) IOT CLUE

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	695025	LED lifespan L90B10 [h]:	38000
Light source:	LED module	Beam angle [°]:	120
Rated power of the luminaire [W]:	108	Light distribution type:	symmetric
Luminous flux [lm]:	14700	Efficiency of the luminaire:	0.89
Supply voltage [V]:	220 - 240	Diffuser material:	glass
Frequency [Hz]:	50 - 60	Diffuser type:	transparent
Luminous efficacy [lm/W]:	136	Material of the body:	aluminium
Energy efficiency class:	C	Colour of the body:	anthracite grey
Electrical protection class:	I	Dimensions (H/W/T/S) [mm]:	321/424/37
Colour temperature [K]:	5000	Impact resistance:	IK09
Colour rendering index:	> 80	Ingress protection:	IP66
SDCM:	≤ 3	Working temperature [°C]:	from -20 to +35
LED lifespan L70B50 [h]:	125000	DIMM DALI:	yes
LED lifespan L80B20 [h]:	79000	Dimensions of single box [mm]:	500/500/95

Card creation date: 17 January 2023  
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 450/2023