

# ARENA LED 1205MM 17650LM 830 IP65 PC 141W

DETAILED CARD



## TECHNICAL PARAMETERS

Light source:	LED module
Rated power of the luminaire [W]*:	141
Luminous flux [lm]*:	17650
Supply voltage [V]:	220-240
Luminous efficacy [lm/W]:	125
Energy efficiency class:	D
Electrical protection class:	I
Colour temperature [K]:	3000
Impact resistance:	IK09
Ingress protection:	IP65

## CHARACTERISTICS

The highly energy-efficient Arena Led lamp features a wide range of luminous flux from 8950 lm to 18400 lm. Such a wide range makes it possible to choose a version tailored to the requirements for lighting a room. The lamp body made of steel sheet, powder-coated in white, and the transparent polycarbonate diffuser provide it with a very high IK09 impact resistance factor. The lamp is also distinguished by a very high IP65 tightness, which allows it to be installed and work in dusty and high humidity conditions. It also meets the highest standards for lamps mounted in industrial premises. Its glare factor is UGR<22 and it is suitable for use with DIMM DALI control.

## APPLICATION

Arena Led is designed for surface or pendant mounting inside facilities. Its characteristics and high value of impact resistance and tightness parameters predispose it to use in industrial halls and facilities with unfavorable conditions (increased dust and humidity, high probability of exposure to impact).

Arena Led lamps will also perform well in sports facilities. They will show resistance to the strongest impacts of the ball or other sports accessories.

# ARENA LED 1205MM 17650LM 830 IP65 PC 141W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE


Index:	483165	Beam angle [°]:	70
EAN:	5905963483165	Surge protection [kV]:	2
Light source:	LED module	Diffuser material:	PC
Rated power of the luminaire [W]:	141	Diffuser type:	transparent
Luminous flux [lm]:	17650	Optics material:	PC
Supply voltage [V]:	220-240	Optics:	lens
Frequency [Hz]:	50-60	Material of the body:	powder coated steel
Luminous efficacy [lm/W]:	125	Colour of the body:	white
Energy efficiency class:	D	Dimensions (H/W/T/S) [mm]:	1205/195/95
Electrical protection class:	I	Impact resistance:	IK09
Colour temperature [K]:	3000	Ingress protection:	IP65
Colour rendering index:	80	Mounting version:	surface, suspended
SDCM:	≤ 3	Working temperature [°C]:	from -20 to +35
Power factor:	0.98	Category type:	luminaires and linear systems
LED lifespan L70B50 [h]:	182000	CE certificate:	<a href="#">162/2023</a>
LED lifespan L80B20 [h]:	115000	Manual:	<a href="#">Download PDF</a>
LED lifespan L90B10 [h]:	55000	Plik LDT:	<a href="#">Download</a>

# ARENA LED 1205MM 17650LM 830 IP65 PC 141W


DETAILED CARD

## ACCESSORIES AVAILABLE


index	Name
483271	ARENA LED safety net 810mm mesh 51mm
483257	ARENA LED protective net 810mm mesh 30mm
483288	ARENA LED safety net 1205mm mesh 51mm
483264	ARENA LED safety net 1205mm 30mm mesh
483240	ARENA LED - RCR sensor - set




ARENA LED safety net 810mm mesh 51mm (483271)




ARENA LED protective net 810mm mesh 30mm (483257)



ARENA LED safety net 1205mm mesh 51mm (483288)



ARENA LED safety net 1205mm 30mm mesh (483264)



ARENA LED - RCR sensor - set (483240)

Card creation date: 08 January 2025  
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 162/2023