BARIS 52 LED DIR/IND IOT BT PIR HYT 1423MM 3900/2700LM 840 IP20 I CL. DALI PRM BLACK 36W/22W SINGLE SENSOR + POWER CORD 3P WITH SWITCH

DETAILED CARD





TECHNICAL PARAMETERS

Ingress protection:	IP40
Impact resistance:	IK06
Nominal power [W]:	58
Luminous flux [lm]*:	6600
Colour temperature [K]:	4000
Material of the body:	aluminium
Colour of the body:	black
Diffuser material:	PC
Diffuser type:	PRM
Mounting version:	suspended

CHARACTERISTICS

Baris 52 LED IoT is a modern suspended lamp that combines elegant design with advanced technology. The modular design makes it easy to service and the unique suspension system ensures simple installation. Available with mounting box or optional

socket

characteristicsThe IoT BT PIR HYT DALI version has: a built-inBT HYT module that allows you to program functions in the Lena Lighting Clue app and control in real time; PIR motion and daylight sensor and DALI driver for dimming the light source.

APPLICATION

The luminaire is dedicated to indoor use. It is used as a source of light for offices requiring focussed eyesight where low UGR and illumination of dark areas (e.g. ceilings) are required. The unique design, energy-efficient LED modules, and the possibility of cooperation with external lighting control systems in the DALI standard dedicate the luminaire to be used in modern office buildings of A+ class, with particular consideration for offices, representative rooms, conference halls, and passageways.

Baris 52 LED Single Clue IoT, as the name suggests, is a single luminaire with a pre-determined length. To create a line of length up to 6 meters without joining the profile and up to 25 meters without joining the diffuser allows version BARIS 52 LED.



BARIS 52 LED DIR/IND IOT BT PIR HYT 1423MM 3900/2700LM 840 IP20 I CL. DALI PRM BLACK 36W/22W SINGLE SENSOR + POWER CORD 3P WITH SWITCH

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	932120
EAN:	5905963932120
Light source:	LED module
Rated power of the luminaire [W]:	58
Luminous flux [Im]:	6600
Supply voltage [V]:	220-240
Frequency [Hz]:	50-60
Luminous efficacy [lm/W]:	115
Energy efficiency class:	E
Electrical protection class:	1
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
LED lifespan L70B50 [h]:	111500
LED lifespan L80B20 [h]:	70400
LED lifespan L90B10 [h]:	34000
Diffuser material:	PC
Diffuser type:	PRM
Diffuser colour:	transparent

Optics:	no
Material of the body:	aluminium
Colour of the body:	black
Dimensions (H/W/T/S) [mm]:	1423/69/52
Impact resistance:	IK06
Ingress protection:	IP40
Mounting version:	suspended
Working temperature [°C]:	from -25 to +35
DIMM DALI:	yes
Version:	BT PIR HYT DALI
Wire type:	5x0.75
Cable length [m]:	1.50
Net weight [kg]:	2.800
UGR (4H8H):	19
Warranty [years]:	5
CE certificate:	441/2023
PZH certificate:	B-BK-60112-0357/2023
Manual:	Download PDF

Card creation date: 10 January 2025





