

TERRANO S 570X48MM 2300LM 830 I KL. BLACK 60D (22W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	577024
Rated power of the luminaire [W]*:	22
Luminous flux [lm]*:	2300
Luminous efficacy [lm/W]:	105
Energy efficiency class:	E
Electrical protection class:	I
Colour temperature [K]:	3000
Beam angle [°]:	60

CHARACTERISTICS

The new Terrano S linear luminaire, thanks to the use of the latest generation of LED modules, is characterized by energy efficiency and excellent technical parameters. Equipped with focusing lenses, Terrano S lamps are sight-friendly and effectively reduce glare (UGR of 12-19). Mounted in a busbar system, they are available in two color temperatures of 3000 K and 4000 K and two color versions: white and black.

DALI version available on request.

APPLICATION

Mounting on a rail system, increases the range of applications of this lamp and allows the user to make rearrangements, even after installation. The lamp has an adapter equipped with mechanical catches that make it easy to plug in, unplug and move the lamps, while ensuring that the fixture is securely held in the rail. The lamps, together with appropriately selected rails and components, allow for ceiling or wall mounting. The Terrano S lamp is perfect as a source of light in offices, stores, dressing rooms, in passageways.

TERRANO S 570X48MM 2300LM 830 I KL. BLACK 60D (22W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	577024	Diffuser colour:	transparent
EAN:	5905963577024	Optics:	lens
Light source:	LED module	Optics material:	PC
Rated power of the luminaire [W]:	22	Material of the body:	powder coated steel
Luminous flux [lm]:	2300	Colour of the body:	black
Luminous efficacy [lm/W]:	105	Dimensions (H/W/T/S) [mm]:	48/566/69
Energy efficiency class:	E	Ingress protection:	IP20
Electrical protection class:	I	Mounting version:	track
Colour temperature [K]:	3000	Working temperature [°C]:	from -10 to +35
Colour rendering index:	>80	Net weight [kg]:	1.120
SDCM:	≤ 3	CE certificate:	303/2023
Beam angle [°]:	60	Manual:	Download PDF
Light distribution type:	symmetric	Category type:	louvres
Diffuser material:	PC	Warranty [years]:	5
Diffuser type:	matrix led		

LIGHT CURVES



Card creation date: 10 July 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 303/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl