

RQ 220 LED N 1900LM 840 IP20 II CL. MAT 17W

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---|------|
| Rated power of the luminaire [W]*: | 17 |
| Luminous flux [lm]*: | 1900 |
| Luminous efficacy [lm/W]: | 112 |
| Energy efficiency class: | E |
| Electrical protection class: | II |
| Colour temperature [K]: | 4000 |
| Colour rendering index: | >80 |
| Beam angle [°]: | 110 |
| Diffuser type: | MAT |
| Material of the body: | ABS |

CHARACTERISTICS

RQ 220 LED N is a new line of round downlights. Designed from the ground up, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The diffuser provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

APPLICATION

Designed from scratch, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The lampshade provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting. The lamp is especially recommended for office spaces, spacious corridors and public spaces.


RQ 220 LED N 1900LM 840 IP20 II CL. MAT 17W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|---------------|---------------------------|--------------------------------------|
| Index: | 947131 | Mounting dimensions [mm]: | rostaw otworów50x50, śruba □5,5mm |
| EAN: | 5905963947131 | Impact resistance: | IK07 |
| Light source: | LED module | Ingress protection: | IP20 |
| Rated power of the luminaire [W]: | 17 | Mounting version: | surface |
| Luminous flux [lm]: | 1900 | Working temperature [°C]: | from 0 to +35 |
| Luminous efficacy [lm/W]: | 112 | Category type: | downlights |
| Energy efficiency class: | E | LED lifespan L70B50 [h]: | 92000 |
| Electrical protection class: | II | LED lifespan L80B20 [h]: | 58000 |
| Colour temperature [K]: | 4000 | LED lifespan L90B10 [h]: | 28000 |
| Colour rendering index: | >80 | Warranty [years]: | 5 |
| Beam angle [°]: | 110 | HACCP: | 852/2004 |
| Diffuser material: | PC | CE certificate: | 298/2023 |
| Diffuser type: | MAT | Manual: | Download PDF |
| Material of the body: | ABS | Plik LDT: | Download |
| Colour of the body: | white | | |
| Dimensions (H/W/T/S) [mm]: | 227/227/86 | | |

LIGHT CURVES



RQ 220 LED N 1900LM 840 IP20 II CL. MAT 17W

DETAILED CARD

ACCESSORIES AVAILABLE

| index | Name |
|--------|--|
| 947353 | Suspension RQ220 f100 white ON/OFF. DALI |

Card creation date: 03 February 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 298/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl