## RQ 220 LED N 2200LM 830 IP20 II CL. PRM 17W

**DETAILED CARD** 





### **TECHNICAL PARAMETERS**

Rated power of the luminaire [W]*:	17
Luminous flux [lm]*:	2000
Luminous efficacy [lm/W]:	118
Energy efficiency class:	D
Electrical protection class:	II
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
Beam angle [°]:	115
Diffuser type:	PRM
Material of the body:	ABS

#### **CHARACTERISTICS**

RQ 220 LED N is a new line of round downlights. Designed from the ground up, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The diffuser provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

### APPLICATION

Designed from scratch, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The lampshade provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting. The lamp is especially recommended for office spaces, spacious corridors and public spaces.



# **RQ 220 LED N 2200LM 830 IP20 II CL. PRM 17W**

**DETAILED CARD** 

### **TECHNICAL PARAMETERS TABLE**

Index:	947162
EAN:	5905963947162
Light source:	LED module
Rated power of the luminaire [W]:	17
Luminous flux [lm]:	2000
Luminous efficacy [lm/W]:	118
Energy efficiency class:	D
Electrical protection class:	II
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
Beam angle [°]:	115
Diffuser material:	PC
Diffuser type:	PRM
Material of the body:	ABS
Colour of the body:	white

Dimensions (H/W/T/S) [mm]:	227/227/86
Mounting dimensions [mm]:	50x50
Impact resistance:	IK07
Ingress protection:	IP20
Mounting version:	surface
Working temperature [°C]:	from 0 to +35
Category type:	downlights
LED lifespan L70B50 [h]:	92000
LED lifespan L80B20 [h]:	58000
LED lifespan L90B10 [h]:	28000
Warranty [years]:	5
HACCP:	<u>852/2004</u>
CE certificate:	<u>298/2023</u>
Manual:	Download PDF
Plik LDT:	Download



# **RQ 220 LED N 2200LM 830 IP20 II CL. PRM 17W**

**DETAILED CARD** 

#### **ACCESSORIES AVAILABLE**

index	Name
947353	Suspension RQ220 fi100 white ON/OFF. DALI

Card creation date: 29 September 2025



