

RQ 220 LED N 2200LM DALI 830 IP20 II CL. PRM 17W

DETAILED CARD



TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	17
Luminous flux [lm]*:	2000
Luminous efficacy [lm/W]:	118
Energy efficiency class:	D
Electrical protection class:	II
Colour temperature [K]:	3000
Colour rendering index:	>80
Beam angle [°]:	115
Diffuser type:	PRM
Material of the body:	ABS

CHARACTERISTICS

RQ 220 LED N is a new line of round downlights. Designed from the ground up, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The diffuser provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

APPLICATION

Designed from scratch, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The lampshade provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting. The lamp is especially recommended for office spaces, spacious corridors and public spaces.


RQ 220 LED N 2200LM DALI 830 IP20 II CL. PRM 17W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	947186	DIMM DALI:	yes
EAN:	5905963947186	Mounting dimensions [mm]:	rostaw otworów50x50, śruba □5,5mm
Light source:	LED module	Impact resistance:	IK07
Rated power of the luminaire [W]:	17	Ingress protection:	IP20
Luminous flux [lm]:	2000	Mounting version:	surface
Luminous efficacy [lm/W]:	118	Working temperature [°C]:	from 0 to +35
Energy efficiency class:	D	Category type:	downlights
Electrical protection class:	II	LED lifespan L70B50 [h]:	92000
Colour temperature [K]:	3000	LED lifespan L80B20 [h]:	58000
Colour rendering index:	>80	LED lifespan L90B10 [h]:	28000
Beam angle [°]:	115	Warranty [years]:	5
Diffuser material:	PC	HACCP:	852/2004
Diffuser type:	PRM	CE certificate:	298/2023
Material of the body:	ABS	Manual:	Download PDF
Colour of the body:	white	Plik LDT:	Download
Dimensions (H/W/T/S) [mm]:	227/227/86		

LIGHT CURVES



RQ 220 LED N 2200LM DALI 830 IP20 II CL. PRM 17W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
947353	Suspension RQ220 f100 white ON/OFF. DALI

Card creation date: 03 February 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 298/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl