# RQ 220 LED N 1800LM 830 IP20 I CL. EM3H MAT 17W

DETAILED CARD



## TECHNICAL PARAMETERS

| | |
|---|---|
| **Rated power of the luminaire [W]*:** | 17 |
| **Luminous flux [lm]*:** | 1800 |
| **Luminous efficacy [lm/W]:** | 106 |
| **Energy efficiency class:** | E |
| **Electrical protection class:** | I |
| **Colour temperature [K]:** | 3000 |
| **Color rendering index (Ra) >:** | 80 |
| **Beam angle [°]:** | 110 |
| **Diffuser type:** | matt |
| **Material of the body:** | ABS |

## CHARACTERISTICS

RQ 220 LED N is a new line of round downlights. Designed from the ground up, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The diffuser provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

## APPLICATION

Designed from scratch, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The lampshade provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.The lamp is especially recommended for office spaces, spacious corridors and public spaces.

# RQ 220 LED N 1800LM 830 IP20 I CL. EM3H MAT 17W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

| | |
|---|---|
| **Index:** | 947209 |
| **EAN:** | 5905963947209 |
| **Light source:** | LED module |
| **Rated power of the luminaire [W]:** | 17 |
| **Luminous flux [lm]:** | 1800 |
| **Luminous efficacy [lm/W]:** | 106 |
| **Energy efficiency class:** | E |
| **Electrical protection class:** | I |
| **Colour temperature [K]:** | 3000 |
| **Color rendering index (Ra) >:** | 80 |
| **Beam angle [°]:** | 110 |
| **Diffuser material:** | PC |
| **Diffuser type:** | matt |
| **Material of the body:** | ABS |
| **Colour of the body:** | white |
| **Dimensions (H/W/T/S) [mm]:** | 227/227/86 |

| | |
|---|---|
| **Mounting dimensions [mm]:** | rostaw otworów50x50, śruba ø5,5mm |
| **Impact resistance:** | IK07 |
| **Ingress protection:** | IP20 |
| **Mounting version:** | surface |
| **Working temperature [°C]:** | from 0 to +25 |
| **Category type:** | downlights |
| **LED lifespan L70B50 [h]:** | 150000 |
| **LED lifespan L80B10 [h]:** | 100000 |
| **LED lifespan L90B10 [h]:** | 50000 |
| **Autotest:** | yes |
| **Warranty [years]:** | 2 |
| **HACCP:** | 852/2004 |
| **CE certificate:** | 298/2023 |
| **Environmental Product Declaration (EPD):** | 944/2026 |
| **Manual:** | Download PDF |
| **ISO Certificates:** | 9001:2015. 14001:2015. 45001:2018. 50001:2018 |

# RQ 220 LED N 1800LM 830 IP20 I CL. EM3H MAT 17W

DETAILED CARD

## ACCESSORIES AVAILABLE

| index | Name |
|---|---|
| 947353 | Suspension RQ220 fi100 white ON/OFF. DALI |



The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 298/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl