

RQ 220 LED PLUS N 2220LM 840 IP20 I CL. AW3H MAT 17W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	947391
Rated power of the luminaire [W]*:	17
Luminous flux [lm]*:	2200
Luminous efficacy [lm/W]:	130
Energy efficiency class:	D
Electrical protection class:	I
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
Diffuser material:	PC
Diffuser type:	mat

CHARACTERISTICS

RQ 220 LED N PLUS is a new line of round downlights. Designed from the ground up, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The diffuser provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

APPLICATION

Designed from scratch, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The lampshade provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting. The lamp is especially recommended for office spaces, spacious corridors and public spaces.

RQ 220 LED PLUS N 2220LM 840 IP20 I CL. AW3H MAT 17W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	947391	Dimensions (H/W/T/S) [mm]:	227/227/86
EAN:	5905963947391	Mounting dimensions [mm]:	rostaw otworów50x50, śruba ø5,5mm
Light source:	LED module	Impact resistance:	IK07
Rated power of the luminaire [W]:	17	Ingress protection:	IP20
Luminous flux [lm]:	2200	Mounting version:	surface
Supply voltage [V]:	220-240	Number on the palette [pcs]:	255
Frequency [Hz]:	50-60	Category type:	downlights
Luminous efficacy [lm/W]:	130	LED lifespan L80B10 [h]:	84000
Energy efficiency class:	D	LED lifespan L70B50 [h]:	132000
Electrical protection class:	I	LED lifespan L90B10 [h]:	42000
Colour temperature [K]:	4000	Autotest:	yes
Beam angle [°]:	110	Warranty [years]:	2
Diffuser material:	PC	CE certificate:	297/2023
Diffuser type:	matt	HACCP:	852/2004
Material of the body:	ABS	Manual:	Download PDF
Colour of the body:	white		

RQ 220 LED PLUS N 2220LM 840 IP20 I CL. AW3H MAT 17W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
947353	Suspension RQ220 f100 white ON/OFF. DALI

Card creation date: 29 September 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 297/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl