RQ 220 LED P 2400LM 840 IP65/IP20 I CL. AW3H PRM 19W

DETAILED CARD





TECHNICAL PARAMETERS

| Rated power of the luminaire [W]*: | 19 |
|------------------------------------|-------|
| Luminous flux [lm]*: | 2400 |
| Luminous efficacy [lm/W]: | 127 |
| Energy efficiency class: | D |
| Electrical protection class: | I |
| Colour temperature [K]: | 4000 |
| Diffuser material: | PC |
| Diffuser type: | PRM |
| Material of the body: | ABS |
| Colour of the body: | white |

CHARACTERISTICS

RQ 220 LED P is a new line of round downlights. Designed from the ground up, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The diffuser provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

APPLICATION

Designed from scratch, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The lampshade provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

The lamp is especially recommended for office spaces, spacious corridors and public spaces.



RQ 220 LED P 2400LM 840 IP65/IP20 I CL. AW3H PRM 19W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| Index: | 979248 |
|-----------------------------------|---------------|
| EAN: | 5905963979248 |
| Light source: | LED module |
| Rated power of the luminaire [W]: | 19 |
| Luminous flux [Im]: | 2400 |
| Supply voltage [V]: | 220-240 |
| Frequency [Hz]: | 50-60 |
| Luminous efficacy [lm/W]: | 127 |
| Energy efficiency class: | D |
| Electrical protection class: | I |
| Colour temperature [K]: | 4000 |
| Color rendering index (Ra) >: | 80 |
| Beam angle [°]: | 115 |
| Diffuser material: | PC |
| Diffuser type: | PRM |
| Material of the body: | ABS |
| Colour of the body: | white |

| Dimensions (H/W/T/S) [mm]: | 221/221/51 |
|------------------------------|---------------------|
| Mounting dimensions [mm]: | 200 |
| Impact resistance: | IK07 |
| Ingress protection: | IP65/IP20 |
| Mounting version: | recessed |
| Working temperature [°C]: | from 0 to +25 |
| Emergency lighting [h]: | 3 |
| Number on the palette [pcs]: | 130 |
| Net weight [kg]: | 0.820 |
| Category type: | downlights |
| LED lifespan L80B20 [h]: | 58000 |
| LED lifespan L70B50 [h]: | 92000 |
| LED lifespan L90B10 [h]: | 28000 |
| Warranty [years]: | 2 |
| CE certificate: | 299/2023 |
| HACCP: | 852/2004 |
| Manual: | <u>Download PDF</u> |

Card creation date: 09 January 2025



