

# RQ 220 LED P 2650LM 830 IP65/IP20 I CL. AW3H PRM 23W

DETAILED CARD



## TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	11
Luminous flux [lm]*:	max 2800
Energy efficiency class:	D; E
Electrical protection class:	I; II
Colour temperature [K]:	3000; 4000
Diffuser material:	PC
Diffuser type:	MAT; OPAL; PRM
Material of the body:	ABS; ABS + aluminium
Colour of the body:	biały

## CHARACTERISTICS

RQ 220 LED P is a new line of round downlights. Designed from the ground up, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The diffuser provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

## APPLICATION

Designed from scratch, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The lampshade provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

The lamp is especially recommended for office spaces, spacious corridors and public spaces.

# RQ 220 LED P 2650LM 830 IP65/IP20 I CL. AW3H PRM 23W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	x	Impact resistance:	IK07
EAN:	x	Ingress protection:	IP65/IP20
Light source:	moduł LED	Mounting version:	podtynkowy
Rated power of the luminaire [W]:	11	Working temperature [°C]:	od 0 do +25; od 0 do +35
Luminous flux [lm]:	max 2800	Emergency lighting [h]:	3
Supply voltage [V]:	220-240	Number on the palette [pcs]:	28; 130; 285
Frequency [Hz]:	50-60	Net weight [kg]:	0.330; 0.380; 0.820; 1.400; 1.450
Energy efficiency class:	D; E	DIMM DALI:	yes
Electrical protection class:	I; II	Category type:	downlights
Colour temperature [K]:	3000; 4000	LED lifespan L80B20 [h]:	58000; 60000
Colour rendering index:	>80; >90	LED lifespan L70B50 [h]:	92000
Beam angle [°]:	110; 115	LED lifespan L90B10 [h]:	28000
Diffuser material:	PC	Version:	Trio (3 sztuki)
Diffuser type:	MAT; OPAL; PRM	Warranty [years]:	2; 5
Material of the body:	ABS; ABS + aluminium	CE certificate:	<a href="#">299/2023; 300/2023</a>
Colour of the body:	biały	HACCP:	<a href="#">852/2004</a>
Dimensions (H/W/T/S) [mm]:	221/221/51	Manual:	<a href="#">Download PDF</a>
Mounting dimensions [mm]:	200		

Card creation date:15 April 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 299/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)