

RQ 220 LED P 2100LM DALI 840 IP65/IP20 II CL. MAT 19W

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---|-------|
| Rated power of the luminaire [W]*: | 19 |
| Luminous flux [lm]*: | 2100 |
| Luminous efficacy [lm/W]: | 111 |
| Energy efficiency class: | E |
| Electrical protection class: | II |
| Colour temperature [K]: | 4000 |
| Diffuser material: | PC |
| Diffuser type: | MAT |
| Material of the body: | ABS |
| Colour of the body: | white |

CHARACTERISTICS

RQ 220 LED P is a new line of round downlights. Designed from the ground up, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The diffuser provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

APPLICATION

Designed from scratch, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The lampshade provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

The lamp is especially recommended for office spaces, spacious corridors and public spaces.

RQ 220 LED P 2100LM DALI 840 IP65/IP20 II CL. MAT 19W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|--|---------------|-------------------------------------|------------------------------|
| Index: | 979378 | Dimensions (H/W/T/S) [mm]: | 221/221/51 |
| EAN: | 5905963979378 | Mounting dimensions [mm]: | 200 |
| Light source: | LED module | Impact resistance: | IK07 |
| Rated power of the luminaire [W]: | 19 | Ingress protection: | IP65/IP20 |
| Luminous flux [lm]: | 2100 | Mounting version: | recessed |
| Supply voltage [V]: | 220-240 | Working temperature [°C]: | from 0 to +35 |
| Frequency [Hz]: | 50-60 | Number on the palette [pcs]: | 285 |
| Luminous efficacy [lm/W]: | 111 | Net weight [kg]: | 0.380 |
| Energy efficiency class: | E | Category type: | downlights |
| Electrical protection class: | II | LED lifespan L80B20 [h]: | 58000 |
| Colour temperature [K]: | 4000 | LED lifespan L70B50 [h]: | 92000 |
| Colour rendering index: | >80 | LED lifespan L90B10 [h]: | 28000 |
| Beam angle [°]: | 110 | Warranty [years]: | 5 |
| Diffuser material: | PC | CE certificate: | 299/2023 |
| Diffuser type: | MAT | HACCP: | 852/2004 |
| Material of the body: | ABS | Manual: | Download PDF |
| Colour of the body: | white | Plik LDT: | Pobierz |
| DIMM DALI: | 1 | | |

Card creation date: 15 April 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 299/2023