


TRIO 3X RQ 220 LED P 2800LM DALI 840 IP65/IP20 I CL. PRM 23W

DETAILED CARD



TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	23
Luminous flux [lm]*:	2800
Luminous efficacy [lm/W]:	122
Energy efficiency class:	D
Electrical protection class:	I
Colour temperature [K]:	4000
Diffuser material:	PC
Diffuser type:	PRM
Material of the body:	ABS
Colour of the body:	white

CHARACTERISTICS

RQ 220 LED P is a new line of round downlights. Designed from the ground up, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The diffuser provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

APPLICATION

Designed from scratch, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The lampshade provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

The lamp is especially recommended for office spaces, spacious corridors and public spaces.

TRIO 3X RQ 220 LED P 2800LM DALI 840 IP65/IP20 I CL. PRM 23W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	979538	Impact resistance:	IK07
EAN:	5905963979538	Ingress protection:	IP65/IP20
Light source:	LED module	Mounting version:	recessed
Rated power of the luminaire [W]:	23	Working temperature [°C]:	from 0 to +35
Luminous flux [lm]:	2800	Number on the palette [pcs]:	28
Frequency [Hz]:	50-60	Net weight [kg]:	1.450
Luminous efficacy [lm/W]:	122	DIMM DALI:	yes
Energy efficiency class:	D	Category type:	downlights
Electrical protection class:	I	LED lifespan L80B10 [h]:	100000
Colour temperature [K]:	4000	LED lifespan L70B50 [h]:	150000
Color rendering index (Ra) >:	80	LED lifespan L90B10 [h]:	50000
Beam angle [°]:	110	Version:	Trio (3 pieces)
Diffuser material:	PC	Warranty [years]:	5
Diffuser type:	PRM	CE certificate:	300/2023
Material of the body:	ABS	HACCP:	852/2004
Colour of the body:	white	Manual:	Download PDF
Dimensions (H/W/T/S) [mm]:	221/221/51	Plik LDT:	Download
Mounting dimensions [mm]:	200		

Card creation date: 09 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 300/2023