

TRIO 3X RQ 220 LED P 2650LM DALI 830 IP65/IP20 I CL. PRM 23W

DETAILED CARD



TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	23
Luminous flux [lm]*:	2650
Luminous efficacy [lm/W]:	116
Energy efficiency class:	D
Electrical protection class:	I
Colour temperature [K]:	3000
Diffuser material:	PC
Diffuser type:	PRM
Material of the body:	ABS
Colour of the body:	white

CHARACTERISTICS

RQ 220 LED P is a new line of round downlights. Designed from the ground up, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The diffuser provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

APPLICATION

Designed from scratch, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The lampshade provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

The lamp is especially recommended for office spaces, spacious corridors and public spaces.

TRIO 3X RQ 220 LED P 2650LM DALI 830 IP65/IP20 I CL. PRM 23W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	979576	Impact resistance:	IK07
EAN:	5905963979576	Ingress protection:	IP65/IP20
Light source:	LED module	Mounting version:	recessed
Rated power of the luminaire [W]:	23	Working temperature [°C]:	from 0 to +35
Luminous flux [lm]:	2650	Number on the palette [pcs]:	28
Frequency [Hz]:	50-60	Net weight [kg]:	1.450
Luminous efficacy [lm/W]:	116	DIMM DALI:	yes
Energy efficiency class:	D	Category type:	downlights
Electrical protection class:	I	LED lifespan L80B20 [h]:	58000
Colour temperature [K]:	3000	LED lifespan L70B50 [h]:	92000
Colour rendering index:	80	LED lifespan L90B10 [h]:	28000
Beam angle [°]:	110	Version:	Trio (3 pieces)
Diffuser material:	PC	Warranty [years]:	5
Diffuser type:	PRM	CE certificate:	300/2023
Material of the body:	ABS	HACCP:	852/2004
Colour of the body:	white	Manual:	Download PDF
Dimensions (H/W/T/S) [mm]:	221/221/51	Plik LDT:	Download
Mounting dimensions [mm]:	200		

Card creation date: 09 January 2025
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 300/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl