

# RQ 220 LED PLUS P 2700LM 830 IP65/IP20 I CL. AW3H MAT 24W

DETAILED CARD



## TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	24
Luminous flux [lm]*:	2700
Frequency [Hz]:	50-60
Luminous efficacy [lm/W]:	113
Energy efficiency class:	D
Electrical protection class:	I
Colour temperature [K]:	3000
Beam angle [°]:	110
Diffuser material:	PC
Diffuser type:	mat

## CHARACTERISTICS

RQ 220 LED P PLUS is a new line of round downlights. Designed from the ground up, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The diffuser provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

## APPLICATION

Designed from scratch, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The lampshade provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

The lamp is especially recommended for office spaces, spacious corridors and public spaces.

# RQ 220 LED PLUS P 2700LM 830 IP65/IP20 I CL. AW3H MAT 24W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	947049	Colour of the body:	white
EAN:	5905963947049	Dimensions (H/W/T/S) [mm]:	221/221/51
Light source:	LED module	Mounting dimensions [mm]:	200
Rated power of the luminaire [W]:	24	Impact resistance:	IK07
Luminous flux [lm]:	2700	Ingress protection:	IP65/IP20
Supply voltage [V]:	220-240	Mounting version:	recessed
Frequency [Hz]:	50-60	Working temperature [°C]:	from 0 to +25
Luminous efficacy [lm/W]:	113	Number on the palette [pcs]:	130
Energy efficiency class:	D	Net weight [kg]:	0.820
Electrical protection class:	I	Category type:	downlights
Colour temperature [K]:	3000	LED lifespan L70B50 [h]:	132000
Colour rendering index:	80	LED lifespan L80B20 [h]:	84000
Beam angle [°]:	110	LED lifespan L90B10 [h]:	42000
Light distribution type:	lamertian	Warranty [years]:	2
Diffuser material:	PC	CE certificate:	<a href="#">301/2023</a>
Diffuser type:	matt	HACCP:	<a href="#">852/2004</a>
Material of the body:	ABS	Manual:	<a href="#">Download PDF</a>