

RQ 220 LED PLUS P 2700LM DALI 830 IP65/IP20 II CL. MAT 24W

DETAILED CARD



TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	24
Luminous flux [lm]*:	2700
Frequency [Hz]:	50-60
Luminous efficacy [lm/W]:	113
Energy efficiency class:	D
Electrical protection class:	II
Colour temperature [K]:	3000
Beam angle [°]:	110
Diffuser material:	PC
Diffuser type:	MAT

CHARACTERISTICS

RQ 220 LED P PLUS is a new line of round downlights. Designed from the ground up, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The diffuser provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

APPLICATION

Designed from scratch, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The lampshade provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

The lamp is especially recommended for office spaces, spacious corridors and public spaces.

RQ 220 LED PLUS P 2700LM DALI 830 IP65/IP20 II CL. MAT 24W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	947056	Dimensions (H/W/T/S) [mm]:	221/221/51
EAN:	5905963947056	Mounting dimensions [mm]:	200
Light source:	LED module	Impact resistance:	IK07
Rated power of the luminaire [W]:	24	Ingress protection:	IP65/IP20
Luminous flux [lm]:	2700	Mounting version:	recessed
Supply voltage [V]:	220-240	Working temperature [°C]:	from 0 to +35
Frequency [Hz]:	50-60	Number on the palette [pcs]:	285
Luminous efficacy [lm/W]:	113	Net weight [kg]:	0.380
Energy efficiency class:	D	Category type:	downlights
Electrical protection class:	II	LED lifespan L70B50 [h]:	132000
Colour temperature [K]:	3000	LED lifespan L80B20 [h]:	84000
Colour rendering index:	>80	LED lifespan L90B10 [h]:	42000
Beam angle [°]:	110	Warranty [years]:	5
Light distribution type:	lambertian	CE certificate:	301/2023
Diffuser material:	PC	HACCP:	852/2004
Diffuser type:	MAT	Manual:	Download PDF
Material of the body:	ABS	Plik LDT:	
DIMM DALI:	yes		
Colour of the body:	white		

Card creation date: 09 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 301/2023