

# RQ 220 LED PLUS P 3300LM 840 IP65/IP20 I CL. AW3H PRM 24W

DETAILED CARD



## TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	17
Luminous flux [lm]*:	max 3300
Frequency [Hz]:	50-60
Energy efficiency class:	C; D; E
Electrical protection class:	I; II
Colour temperature [K]:	3000; 4000
Beam angle [°]:	110; 115
Diffuser material:	PC
Diffuser type:	MAT; OPAL; PRM

## CHARACTERISTICS

RQ 220 LED P PLUS is a new line of round downlights. Designed from the ground up, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The diffuser provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

## APPLICATION

Designed from scratch, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The lampshade provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

The lamp is especially recommended for office spaces, spacious corridors and public spaces.

# RQ 220 LED PLUS P 3300LM 840 IP65/IP20 I CL. AW3H PRM 24W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	x	Mounting dimensions [mm]:	200
EAN:	x	Impact resistance:	IK07
Light source:	moduł LED	Ingress protection:	IP65/IP20
Rated power of the luminaire [W]:	17	Mounting version:	podtynkowy
Luminous flux [lm]:	max 3300	Working temperature [°C]:	od 0 do +25; od 0 do +35
Supply voltage [V]:	220-240	Number on the palette [pcs]:	28; 130; 285
Frequency [Hz]:	50-60	Product line:	Trio
Energy efficiency class:	C; D; E	DIMM DALI:	yes
Electrical protection class:	I; II	Category type:	downlights
Colour temperature [K]:	3000; 4000	LED lifespan L70B50 [h]:	132000
Colour rendering index:	>80	LED lifespan L80B20 [h]:	84000
Beam angle [°]:	110; 115	LED lifespan L90B10 [h]:	42000
Light distribution type:	lambertowski	Version:	Trio (3 sztuki)
Diffuser material:	PC	Warranty [years]:	2; 5
Diffuser type:	MAT; OPAL; PRM	CE certificate:	<a href="#">11/2023; 301/2023; 302/2023</a>
Material of the body:	ABS	HACCP:	
Colour of the body:	biały	Manual:	<a href="#">Download PDF</a>
Dimensions (H/W/T/S) [mm]:	221/221/51		

Card creation date:15 April 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric andelectronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 301/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)