### **RQ 220 LED N 1900LM DALI 840 IP44 II CL. MAT 17W**

**DETAILED CARD** 





### **TECHNICAL PARAMETERS**

Rated power of the luminaire [W]*:	17
Luminous flux [lm]*:	1900
Luminous efficacy [lm/W]:	112
Energy efficiency class:	Е
Electrical protection class:	II
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
Beam angle [°]:	110
Diffuser type:	matt
Material of the body:	ABS

### **CHARACTERISTICS**

RQ 220 LED N is a new line of round downlights. Designed from the ground up, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The diffuser provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

### **APPLICATION**

Designed from scratch, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The lampshade provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting. The lamp is especially recommended for office spaces, spacious corridors and public spaces.



# **RQ 220 LED N 1900LM DALI 840 IP44 II CL. MAT 17W**


**DETAILED CARD** 

### **TECHNICAL PARAMETERS TABLE**

Index:	947315
EAN:	5905963947315
Light source:	LED module
Rated power of the luminaire [W]:	17
Luminous flux [lm]:	1900
Luminous efficacy [lm/W]:	112
Energy efficiency class:	E
Electrical protection class:	II
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
Beam angle [°]:	110
Diffuser material:	PC
Diffuser type:	matt
Material of the body:	ABS
Colour of the body:	white

	_
Dimensions (H/W/T/S) [mm]:	232/232/100
Mounting dimensions [mm]:	rostaw otworów 180x180,śruba ø4,5mm
Impact resistance:	IK07
Ingress protection:	IP44
Mounting version:	surface
Working temperature [°C]:	from 0 to +35
DIMM DALI:	yes
Category type:	downlights
LED lifespan L70B50 [h]:	60 000
Warranty [years]:	5
HACCP:	<u>852/2004</u>
CE certificate:	31/2025
Manual:	Download PDF
Plik LDT:	Download

### **LIGHT CURVES**





## **RQ 220 LED N 1900LM DALI 840 IP44 II CL. MAT 17W**

**DETAILED CARD** 

### **ACCESSORIES AVAILABLE**

index	Name
947353	Suspension RQ220 fi100 white ON/OFF. DALI

Card creation date: 29 September 2025





Page 3/3