

RQ 220 LED PLUS N 2050LM 830 IP44 II CL. MAT 17W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	947520
Rated power of the luminaire [W]*:	17
Luminous flux [lm]*:	2050
Luminous efficacy [lm/W]:	121
Energy efficiency class:	D
Electrical protection class:	II
Colour temperature [K]:	3000
Colour rendering index:	>80
Diffuser material:	PC
Diffuser type:	MAT

CHARACTERISTICS

RQ 220 LED N PLUS is a new line of round downlights. Designed from the ground up, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The diffuser provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

APPLICATION

Designed from scratch, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The lampshade provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting. The lamp is especially recommended for office spaces, spacious corridors and public spaces.


RQ 220 LED PLUS N 2050LM 830 IP44 II CL. MAT 17W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	947520	Colour of the body:	white
EAN:	5905963947520	Dimensions (H/W/T/S) [mm]:	232/232/100
Light source:	LED module	Mounting dimensions [mm]:	rostaw otworów 180x180, śruba □4,5mm
Rated power of the luminaire [W]:	17	Impact resistance:	IK07
Luminous flux [lm]:	2050	Mounting version:	surface
Supply voltage [V]:	220-240	Number on the palette [pcs]:	120
Frequency [Hz]:	50-60	Category type:	downlights
Luminous efficacy [lm/W]:	121	LED lifespan L70B50 [h]:	72 000
Energy efficiency class:	D	Warranty [years]:	5
Electrical protection class:	II	CE certificate:	297/2023
Colour temperature [K]:	3000	HACCP:	852/2004
Beam angle [°]:	110	Manual:	Download PDF
Diffuser material:	PC	Plik LDT:	Download
Diffuser type:	MAT		
Ingress protection:	IP44		
Material of the body:	ABS		

LIGHT CURVES



RQ 220 LED PLUS N 2050LM 830 IP44 II CL. MAT 17W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
947353	Suspension RQ220 f100 white ON/OFF. DALI

Card creation date: 03 February 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 297/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl