### RQ 220 LED PLUS N 2300LM 830 IP44 II CL. PRM 17W

**DETAILED CARD** 





### **TECHNICAL PARAMETERS**

Index:	947575
Rated power of the luminaire [W]*:	17
Luminous flux [lm]*:	2300
Luminous efficacy [lm/W]:	136
Energy efficiency class:	D
Electrical protection class:	II
Colour temperature [K]:	3000
Colour rendering index:	80
Diffuser material:	PC
Diffuser type:	PRM

### **CHARACTERISTICS**

RQ 220 LED N PLUS is a new line of round downlights. Designed from the ground up, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The diffuser provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

### APPLICATION

Designed from scratch, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The lampshade provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting. The lamp is especially recommended for office spaces, spacious corridors and public spaces.



# **RQ 220 LED PLUS N 2300LM 830 IP44 II CL. PRM 17W**

**DETAILED CARD** 

### **TECHNICAL PARAMETERS TABLE**

Index:	947575
EAN:	5905963947575
Light source:	LED module
Rated power of the luminaire [W]:	17
Luminous flux [lm]:	2300
Supply voltage [V]:	220-240
Frequency [Hz]:	50-60
Luminous efficacy [lm/W]:	136
Energy efficiency class:	D
Electrical protection class:	II
Colour temperature [K]:	3000
Beam angle [°]:	110
Diffuser material:	PC
Diffuser type:	PRM
Material of the body:	ABS

Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	232/232/100
Mounting dimensions [mm]:	rostaw otworów 180x180,śruba ø4,5mm
Impact resistance:	IK07
Ingress protection:	IP44
Mounting version:	surface
Number on the palette [pcs]:	120
Category type:	downlights
LED lifespan L70B50 [h]:	72 000
Warranty [years]:	5
CE certificate:	30/2025
HACCP:	<u>852/2004</u>
Manual:	Download PDF
Plik LDT:	Download



## **RQ 220 LED PLUS N 2300LM 830 IP44 II CL. PRM 17W**

**DETAILED CARD** 

#### **ACCESSORIES AVAILABLE**

index	Name
947353	Suspension RQ220 fi100 white ON/OFF. DALI

Card creation date: 03 February 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

