

# RQ 220 LED PLUS N 2300LM DALI 830 IP44 II CL. PRM 17W

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	947605
<b>Rated power of the luminaire [W]*:</b>	17
<b>Luminous flux [lm]*:</b>	2300
<b>Luminous efficacy [lm/W]:</b>	136
<b>Energy efficiency class:</b>	D
<b>Electrical protection class:</b>	II
<b>Colour temperature [K]:</b>	3000
<b>Colour rendering index:</b>	>80
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	PRM

## CHARACTERISTICS

RQ 220 LED N PLUS is a new line of round downlights. Designed from the ground up, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The diffuser provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

## APPLICATION

Designed from scratch, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The lampshade provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting. The lamp is especially recommended for office spaces, spacious corridors and public spaces.

# RQ 220 LED PLUS N 2300LM DALI 830 IP44 II CL. PRM 17W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	947605	Colour of the body:	white
EAN:	5905963947605	DIMM DALI:	yes
Light source:	LED module	Emergency lighting [h]:	3
Rated power of the luminaire [W]:	17	Dimensions (H/W/T/S) [mm]:	232/232/100
Luminous flux [lm]:	2300	Mounting dimensions [mm]:	rostaw otworów 180x180, śruba □4,5mm
Supply voltage [V]:	220-240	Impact resistance:	IK07
Frequency [Hz]:	50-60	Mounting version:	surface
Luminous efficacy [lm/W]:	136	Number on the palette [pcs]:	120
Energy efficiency class:	D	Category type:	downlights
Electrical protection class:	II	LED lifespan L70B50 [h]:	72 000
Colour temperature [K]:	3000	Warranty [years]:	5
Beam angle [°]:	110	CE certificate:	<a href="#">297/2023</a>
Diffuser material:	PC	HACCP:	<a href="#">852/2004</a>
Diffuser type:	PRM	Manual:	<a href="#">Download PDF</a>
Ingress protection:	IP44		
Material of the body:	ABS		

# RQ 220 LED PLUS N 2300LM DALI 830 IP44 II CL. PRM 17W

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
947353	Suspension RQ220 f100 white ON/OFF. DALI

Card creation date: 03 February 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 297/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl